TECHNICAL SPECIFICATION

2m Adjustable Work Positioning Lanyard with Rope Grab

2m Adjustable Work Positioning Lanyard with Rope Grab / FAR0420



DESCRIPTION

2m work positioning lanyard with non-openable aluminium rope grab with 2 screw gate connectors in alloy steel. Rope ends stitched and covered with polyethylene protective sleeve.

OPTIONS

2m Adjustable Work Positioning Lanyard with Rope Grab (FAR0420)

SAFETY STANDARDS

EN 358

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Length
2m Max.

Material
12mm High Quality Kernmantle Rope

Rope Ends
Stitched and Covered With Polyethylene Protective Sleeve. Abrasion Resistant Thimbles Provided Within Loops

Protective Rope Sleeve
60cm

Adjustment Device
Non Openable Rope Grab, Aluminium

Product Weight
1900g

Delivered With
2 Screwgate Connectors In Alloy Steel. Gate Opening 18mm. Conforms to EN362 Class B & M

DOWNLOADS

Image Pack (ZIP)
doc-far0420-far0421.pdf (PDF)

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.