

3159
OSCILLATING COMPACT ELBOW BSP TAPER STUD

maximum working pressure	**bar** 20	**MPa** 2,0	**psi** 290
working temperature	**°C (Celsius)** From -20 to 80	**F (Farenheit)** From -4 to 176	**K (Kelvin)** From 253 to 353
vacuum capability	**mm Hg** vacuum level of 755,000		

body	engineering grade polymer
sub-base	nickel-plated brass
'O'-rings	nitrile
gripping ring	stainless steel



legris connectic	ØD (mm)	C	E (mm)	F (mm)	ØG (mm)	H (mm)	K (mm)	L (mm)	(kg)
3159 04 10	4	R1/8	7,5	12,0	11,0	22,0	13,0	17,5	0,012
3159 06 10	6	R1/8	7,5	14,0	14,0	26,5	15,0	20,5	0,014
3159 06 13	6	R1/4	11,0	14,0	14,0	23,5	15,0	20,5	0,022
3159 08 10	8	R1/8	7,5	17,0	16,0	32,0	18,5	23,5	0,036
3159 08 13	8	R1/4	11,0	17,0	16,0	29,0	18,5	23,5	0,037
3159 08 17	8	R3/8	11,5	17,0	16,0	25,0	18,5	23,5	0,033
3159 10 13	10	R1/4	11,0	19,0	19,5	37,5	21,0	29,0	0,053
3159 10 17	10	R3/8	11,5	19,0	19,5	33,5	21,0	29,0	0,045
3159 12 13	12	R1/4	11,0	21,0	22,0	44,5	23,0	33,5	0,080
3159 12 17	12	R3/8	11,5	21,0	22,0	41,0	23,0	33,5	0,070