DATASHEET - E59-A18C115C02-CV

Proximity Sensor, M18, analog, Sn=1-15mm, 15-30VDC, 0-20mA, 0-10V, line 2m

Part no. **E59-A18C115C02-CV**
166807

General specifications

Product name	Eaton E59 AccuProx analog inductive proximity sensor
Part no.	E59-A18C115C02-CV
EAN	4015081643660
Product Length/Depth	152.4 millimetre
Product height	44.45 millimetre
Product width	127 millimetre
Product weight	0.45 kilogram
Certifications	UL 508 UL UL File No.: E166051 CSA Class No.: 3211-03 CSA File No.: 50513 IEC/EN 60947-5-2 CSA CE CSA-C22.2 No. 14 UL Category Control No.: NRKH, NRKH7
Product Tradename	E59 AccuProx
Product Type	Analog inductive proximity sensors
Product Sub Type	None
Public Consumption	Yes
Product Family Description	ES-PCD-Eaton E59 AccuProx analog inductive proximity sensors
Globally Marketable	Yes

Product Specification Details

Actuation type	Metallic Target
Ambient operating temperature - max	70 °C
Ambient operating temperature - min	-40 °C
Category (EN 954-1)	B
Connection type	2 m connection cable 3-wire/4-wire
Degree of protection	NEMA 4X, 6, 13 IP67
Diameter sensor	18 mm
Electric connection type	Cable
Enclosure material	Metal
Enclosure material finishing	Other
Enclosure type	Cylinder, screw-thread
Explosion safety category for dust	None
Explosion safety category for gas	None
Installation type	Not flat
Interface type	None
LED indicator	Status indication of Operating voltage: Green LED Status indication of Switching state: Red LED
Material	Stainless steel
Mounting method	Non-flush mounting
Number of contact energized outputs with signalling function	0
Number of outputs (protected contact energized)	0
Number of outputs (protected semiconductor)	0
Number of outputs (semiconductor with signaling function)	0
Output current	0 - 20 mA
Output current at protected output - max	20 mA
Output voltage	0 - 10 V

Product category			E59 AccuProx Series
Rated control supply voltage (Us) at AC, 50 Hz - max			0 V
Rated control supply voltage (Us) at AC, 50 Hz - min			0 V
Rated control supply voltage (Us) at AC, 60 Hz - max			0 V
Rated control supply voltage (Us) at AC, 60 Hz - min			0 V
Rated control supply voltage (Us) at DC - max			30 V
Rated control supply voltage (Us) at DC - min			15 V
Rated switching distance (Sn) - max			15 mm
Rated switching distance (Sn) - min			1 mm
Repeatability			1 %
Safety performance level (EN ISO 13849-1)			None
Sensor height			0 mm
Sensor length			64.5 mm
Shock resistance			30 g, Mechanical, Shock duration 11 ms
SIL (IEC 61508)			None
Supply voltage - max			30 V
Supply voltage - min			15 V
Switch function type			Other
Switching frequency			100 Hz
Switching output type			Analog
Temperature drift of sn			10 %
Type			Inductive sensor
Voltage rating - max			30 V
Voltage type			DC
Width sensor			0 mm

Technical data ETIM 9.0

Sensors (EG000026) / Inductive proximity switch (EC002714)

Electric engineering, automation, process control engineering / Sensor technology, safety-related sensor technology / Safety-related inductive sensor / Safety-related inductive proximity switch (ecl@ss13-27-27-41-01 [AKE630019])

Width sensor		mm	0
Height of sensor		mm	0
Length of sensor		mm	64.5
Diameter sensor		mm	18
Mechanical mounting condition for sensor			Not flat
Switching distance		mm	15
Suitable for safety functions			
Type of switch function			Other
Type of switching output			Other
Type of electric connection			Cable
Number of semiconductor outputs with signalling function			0
Number of contact energized outputs with signalling function			0
Number of protected semiconductor outputs			0
Number of protected contact energized outputs			0
Type of actuation			Metallic Target
Type of interface			None
Type of interface for safety communication			None
Construction type housing			Cylinder, screw-thread
Coating housing			Other
Cascadable			
SIL according to IEC 61508			None
Performance level according to EN ISO 13849-1			None
Max. output current at protected output		mA	20
Supply voltage		V	15 - 30
Rated control supply voltage AC 50 Hz		V	0 - 0
Rated control supply voltage AC 60 Hz		V	0 - 0

Rated control supply voltage DC		V	15 - 30
Voltage type			DC
Switching frequency		Hz	100
With monitoring function downstream switching devices			
Housing material			Metal
Compression-resistant			
Explosion safety category for gas			None
Explosion safety category for dust			None
Interference resistance to magnetic fields			
Degree of protection (NEMA)			4X, 6, 13

© 04/2023 by Eaton Industries GmbH