

## Dimensions




## Model Number

**V1-G-10M-PVC-V1-G**

Connecting cable, M12 to M12, PVC cable 4-pin

## Features

- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Gold plated contacts
- Degree of protection IP67 / IP68 / IP69K
- Suitable for 2-, 3- and 4-wire technology

## Technical data

| | | |
|---|---|---|
| **General specifications** | | |
| Number of pins | | 4 |
| Connection 1 | | socket |
| Construction type 1 | | straight |
| Threading 1 | | M12 |
| Connection 2 | | Male connector |
| Construction type 2 | | straight |
| Threading 2 | | M12 |
| **Electrical specifications** | | |
| Operating voltage | $U_B$ | max. 250 V AC/DC |
| Test voltage | | > 1500 $V_{eff}$ AC |
| Operating current | | max. 4 A |
| Volume resistance | | < 5 mΩ |
| **Ambient conditions** | | |
| Ambient temperature | | cable, fixed: -25 ... 70 °C (-13 ... 158 °F)<br>cable, flexing: -5 ... -70 °C (23 ... -94 °F) |
| Pollution Degree | | 3 |
| **Mechanical specifications** | | |
| Contact elements | | spring-loaded contact socket |
| Pin diameter | | 1 mm |
| Degree of protection | | IP67 / IP68 / IP69k |
| Material | | |
| Contacts | | CuSn / Au |
| Contact surface | | Au |
| Body | | TPU, black |
| Cable | | PVC |
| Slotted nut | | Diecast zinc |
| Sleeve connector | | Diecast zinc |
| Core insolation | | PVC |
| Cable | | fine-strand, flexible |
| Sheath diameter | | Ø 4.8 mm |
| Bending radius | | > 10 x cable diameter, moving |
| Color | | grey |
| Cores | | 4 x 0.34 $mm^2$ |
| Conductor construction | | 19 x 0.15 mm Ø |
| Length | L | 10 m |
| Flammability | | |
| Contact material | | 94 HB |
| Housing | | 94 V-2 |
| **Compliance with standards and directives** | | |
| Standard conformity | | |
| Degree of protection | | EN 60529:2000 |

## Electrical connection




Release date: 2014-07-04 13:38 Date of issue: 2014-07-04 114702_eng.xml

| | |
|---|---|
| Standards | IEC 61076-2-101:2008 |
| Flammability | Grip: UL 94 |

Release date: 2014-07-04 13:38 Date of issue: 2014-07-04 114702_eng.xml



Refer to “General Notes Relating to Pepperl+Fuchs Product Information”.
Pepperl+Fuchs Group www.pepperl-fuchs.com
USA: +1 330 486 0001 fa-info@us.pepperl-fuchs.com
Germany: +49 621 776 4411 fa-info@de.pepperl-fuchs.com
Singapore: +65 6779 9091 fa-info@sg.pepperl-fuchs.com
PEPPERL+FUCHS SENSING YOUR NEEDS