SKINDICHT® SM-PE-M

SKINDICHT® SM-PE-M, counter nuts with cutting edges to cut through the insulating layer, thus guaranteeing an optimum EMC contact



CE

Mechanical resistance

Good chemical resistance

Benefits

Cutting edges cut through the insulating layer, thus guaranteeing an optimum EMC contact
Suitable for all metric glands used in earthing and EMC applications

Application range

For lacquered, anodised or powder-coated housings.

Product Make-up

Metric connection thread acc. to DIN EN 60423
Basis for technical information DIN IEC 62444

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000940 ETIM 5.0 Class-Description: Locknut for cable screw gland
Material:	Nickel-plated brass
Temperature range:	-40 °C to +100 °C

Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

Last Update (11.07.2017)
©2017 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

LAPP GROUP

PRODUCT INFORMATION

SKINDICHT® SM-PE-M

Article number	Article designation / size	Thickness (mm)	SW mm	Outer Ø (mm)
SKINDICHT® SM-PE-M				
52103300	M 12 x 1,5	3.5	15	16.5
52103310	M 16 x 1,5	3.5	19	20.9
52103320	M 20 x 1,5	3.7	24	26.4
52103330	M 25 x 1,5	4.2	30	33
52103340	M 32 x 1,5	4.7	36	39.6
52103350	M 40 x 1,5	5.5	46	50.6
52103360	M 50 x 1,5	5.5	60	66
52103370	M 63 x 1,5	7	70	77
52103371	M 75 x 1,5	8	85	95
52103372	M 90 x 2	10	102	114
52103373	M 110 x 2	12	124	135

Last Update (11.07.2017)
©2017 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16