Translucent Polycarbonate (1591 Series)





Molded in Flame Retardant Polycarbonate

KEY FEATURES

- Electronic instrument enclosures, designed for mounting printed circuit boards.
- Ideally suited for modern styling or where internal components need to be visible.
- Molded in flame retardant translucent polycarbonate (material carries a UL flammability rating of 94V-0).
- Integral card guides accept 1.5 mm (0.062") P.C. cards.
- Lap joint construction provides protection against access of dust and splashing water.
- Designed to meet IP54
- Molded from translucent, ice blue or infrared translucent red polycarbonate. Visit our web site for color & detail photos of each part.
- Lid is secured with M3 x 10 mm Philips machine screws, threaded into tapped integral brass bushings.

ACCESSORIES



P.C. Board Card Adaptors

Allows horizontal mounting of P.C. board(s). **See "Accessories Section" for full details!**

1591Z6 - Package of 6
1591Z50 - Package of 50
1591Z100 - Package of 100



Replacement Screws

Machine screws, nickel plated, M3 - 0.5 x 10mm

1591MS100 - Package of 100



Flange Kits

Mount to either the rear (using glue) or can be attached to the lid using existing lid screws and holes. **See "Accessories Section" for full details!**



Belt or Pocket Clip

Molded from tough nylon, includes 2 nylon screws and mounting template.


1599CLIP - Black
1599CLIPGY - Grey

Hammond Manufacturing Co. Ltd.
394 Edinburgh Rd. North
Guelph, Ontario N1H 1E5 CANADA
Phone: 519-822-2960 Fax: 519-822-0715

www.hammondmfg.com

Hammond Manufacturing Co. Inc.
256 Sonwil Dr.
Cheektowaga, NY 14225 USA
Phone: 716-651-0086 Fax: 716-651-0726

Translucent Polycarbonate (1591 Series)




Lid (Inside & Edge View)

Top View

Part Number		Units	Dimensions					P.C. Card Clearance	
Ice Blue	IR Red		A	B	C (No Lid)	F	G	J	K
1591ATBU	1591ATRD	inch	3.9	2.0	0.8	3.4	1.4	1.1	3.1
		mm	100	50	21	86	36	29	79
1591BTBU	1591BTRD	inch	4.4	2.4	1.1	3.9	1.9	1.6	3.5
		mm	112	62	27	98	48	41	91
1591CTBU	1591CTRD	inch	4.7	2.6	1.4	4.2	2.0	1.7	3.9
		mm	120	65	36	106	51	44	99
1591DTBU	1591DTRD	inch	5.9	3.2	1.8	5.4	2.6	2.3	5.0
		mm	150	80	46	136	66	59	129
1591ETBU	1591ETRD	inch	7.5	4.3	2.2	6.9	3.8	3.5	6.6
		mm	191	110	57	176	96	89	170

NOTES: - Assembled height = dimension “C” + 0.16” (4.0 mm)
- Average wall thickness: 0.06” (1.5 mm)



Same high quality construction as our ABS plastic series (brass inserts & machine screws) for repetitive assembly & disassembly...

Hammond Manufacturing Co. Ltd.
394 Edinburgh Rd. North
Guelph, Ontario N1H 1E5 CANADA
Phone: 519-822-2960 Fax: 519-822-0715

www.hammondmfg.com

Hammond Manufacturing Co. Inc.
256 Sonwil Dr.
Cheektowaga, NY 14225 USA
Phone: 716-651-0086 Fax: 716-651-0726