PRODUCT-DETAILS

XLP00-A60/60-A-3BC-above

XLP00-A60/60-A-3BC-above Fuse Switch Disconnector



General Information

Extended Product Type	XLP00-A60/60-A-3BC-above
Product ID	1SEP101917R0001
EAN	7025840015642
Catalog Description	XLP00-A60/60-A-3BC-above Fuse Switch Disconnector
Long Description	XLP00,3-pole,160A, incl. A60/60 adapter and 3 Bridge Clamps, cable above

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Popular Downloads

Data Sheet, Technical Information	1SEC312012D0201

© 2024 ABB. All rights reserved.

Instructions and Manuals	No Instructions and Manuals needed

Environmental

Degree of Protection	IP30

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85389099
Country of Origin	Bulgaria (BG) China (CN)

Dimensions

Product Net Width	105 mm
Product Net Height	206 mm
Product Net Depth / Length	126 mm
Product Net Weight	0.95 kg

Container Information

Package Level 1 Units	shrink-wrap 1 piece
Package Level 1 Width	105 mm
Package Level 1 Depth / Length	126 mm
Package Level 1 Height	206 mm
Package Level 1 Gross Weight	0.95 kg
Package Level 1 EAN	7025840015642
Package Level 2 EAN	7025840015642

Technical

Degree of Protection	IP30
Device Type Manager (DTM)	Fuseswitchdisconnector
Electronic Fuse Monitoring	No
Fuse Size	NH00 NH000
Fuse System	DIN
Handle Type	Front cover 3P
Mounting Type	60mm Busbar System
Number of Poles	3P
Power Loss	at Rated Load 3.5 W
Rated Conditional Short-Circuit Current (I_{nc})	(690 V) 50 kiloampere rms
Rated Current (I_n)	160 A
Rated Frequency (f)	Main Circuit 50/60 Hz
Rated Impulse Withstand Voltage (U_{imp})	Main Circuit 8 kV
Rated Operational Current AC-21B (I_e)	(690 V) 125 A
Rated Operational Current AC-22B (I_e)	(500 V) 160 A (800 V) 63 A

© 2024 ABB. All rights reserved.

	(1000 V) 125 A
Rated Operational Current AC-23B (I_e)	(400V) 125 A
Rated Operational Voltage	400 V AC 500 V AC 690 V AC 800 V AC 1000 V AC
Rated Voltage (U_r)	400 V AC 500 V AC 690 V AC 800 V AC 1000 V AC
Special Functions	Not Included
Standards	IEC60947-3 GB/T14048.3
Terminal Type	Cable Clamp

Certificates and Declarations

Declaration of Conformity - CE	1SEP500050P0001

Classifications

Object Classification Code	S
ETIM 8	EC001040 - Fuse switch disconnector
ETIM 9	EC001040 - Fuse switch disconnector
eClass	V11.1 : 27371401
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Norway)	1687116

Categories

Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → EasyLine



© 2024 ABB. All rights reserved.