



## jalas® ZENIT 1718

EN ISO 20345:2011 S3, SRC  ASTM F2413-18 M/I/C SD 35 PR

Learn more

A soft, light and ergonomic mid-cut safety boot with BOA® Fit System and highest (S3) level protection. The PU-coated and split leather upper offer water repellent properties and great fit for long days on your feet. An oil-resistant RPU outer sole gives enhanced grip and the ventilated inner sole keeps feet cool. Features our JALAS® aluminium toe cap, steel puncture protection and double impact protection zones in PORON® XRD®.

### CHARACTERISTICS

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

### FUNCTIONS

- ProNose toe reinforcement
- Pull loops
- Water repellent
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)
- Padded boot shaft
- Oil-resistant outsole
- Anti-static properties
- Ventilating insole
- Bellows tongue
- Quick-tie
- Stabilizator



*All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.*

## PREVENTS RISK OF

Toe injuries, nail penetration, antistatic

## PRIMARY ENVIRONMENTS OF USE

Outdoors, all-year use, environments with risk for outsole penetration

## SPECIFICATION

**TYPE** Safety footwear, Boots/Ankle boots
**CATEGORY** Cat. II
**NAIL PROTECTION MATERIAL** Steel
**FITTING** Regular
**COLLECTION** Zenit
**UPPER MATERIAL** PU-coated leather, Split leather
**PRONOSE MATERIAL** PU
**TOECAP MATERIAL** Aluminium
**LINING MATERIAL** Polyester, polyamide
**INSOLE** FX2 Climate
**INNERSOLE MATERIAL** Textile, Soft EVA, Polyester-based conductive thread, Merino wool, Double shock absorption zones in Poron® XRD®
**MIDSOLE MATERIAL** PU midsole
**OUTSOLE MATERIAL** RPU outsole
**FASTENING** BOA® Fit System
**COLOUR** Black, Grey, Red
**NET WEIGHT, (SIZE 42)** 1.39 kg

## COMPLIANCE

CE Cat. II

EN ISO 20345:2011
S3, SRC

EAC
TP TC 019:2011

ASTM F2413-18
M/I/C
SD 35 PR

ÖNORM Z 1259

DGUV 112-191

## FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- ESD
- Aluminium toecap
- Oil-resistant outsole
- ProNose toe reinforcement
- Nail protection in steel
- Water repellent
- Stabilizator

| SIZE | | | | ARTICLE NUMBER | EAN |
|---|---|---|---|---|---|
| EU | UK | US M | US W | | |
| 36 | 3 | 4 | 5 | 1718-36 | 6408487501678 |
| 37 | 4 | 5 | 6 | 1718-37 | 6408487501685 |
| 38 | 5 | 5½ | 6½ | 1718-38 | 6408487501692 |
| 39 | 6 | 6½ | 7½ | 1718-39 | 6408487501708 |
| 40 | 6½ | 7½ | 8½ | 1718-40 | 6408487501715 |
| 41 | 7 | 8 | 9 | 1718-41 | 6408487501722 |
| 42 | 8 | 9 | 10 | 1718-42 | 6408487501739 |
| 43 | 9 | 9½ | 11 | 1718-43 | 6408487501746 |
| 44 | 10 | 10½ | 11½ | 1718-44 | 6408487501753 |
| 45 | 10½ | 11 | 12½ | 1718-45 | 6408487501760 |
| 46 | 11 | 12 | 13 | 1718-46 | 6408487501777 |
| 47 | 12 | 13 | 14 | 1718-47 | 6408487501784 |

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com



*All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.*