PRODUCT-DETAILS

TAE50-30-00RT 17-32V DC

TAE50-30-00RT 17-32V DC Contactor



General Information

Extended Product Type	TAE50-30-00RT 17-32V DC
Product ID	1SBL359060R5100
EAN	3471522244710
Catalog Description	TAE50-30-00RT 17-32V DC Contactor
Long Description	TAE50 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC / 1000 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The TAE..RT contactors are the Ring Tongue terminal version of the TAE... range. The TAE... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: DC operated with standard double-winding DC coils (with add-on factory-mounted lagging contact for insertion of the"holding" winding). TAE... contactors offer a large coil voltage range - Accessories: a wide range of accessories is available.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

© 2024 ABB. All rights reserved.

Data Sheet, Technical Information	1SNC001003C0202
Instructions and Manuals	FPTC407767P0002

Dimensions

Product Net Width	82 mm
Product Net Depth / Length	108 mm
Product Net Height	110 mm
Product Net Weight	1.2 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	0
Rated Operational Voltage	Main Circuit 1000 V
Rated Frequency (f)	Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors Θ = 40 °C 100 A
Rated Operational Current AC-1 (I_e)	(690 V) 40 °C 100 A (690 V) 55 °C 85 A (690 V) 70 °C 70 A
Rated Operational Current AC-3 (I_e)	(415 V) 55 °C 50 A (440 V) 55 °C 45 A (500 V) 55 °C 45 A (690 V) 55 °C 35 A (1000 V) 55 °C 23 A (380 / 400 V) 55 °C 50 A (220 / 230 / 240 V) 55 °C 53
Rated Operational Power AC-3 (P_e)	(415 V) 25 kW (440 V) 25 kW (500 V) 30 kW (690 V) 30 kW (1000 V) 30 kW (380 / 400 V) 22 kW (220 / 230 / 240 V) 15 kW
Rated Breaking Capacity AC-3	8 x Ie AC-3
Rated Making Capacity AC-3	10 x Ie AC-3
Short-Circuit Protective Devices	gG Type Fuses 100 A
Rated Short-time Withstand Current Low Voltage (I_{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 650 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 110 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 250 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1000 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 370 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 440 V 1300 A cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 690 V 630 A
Maximum Electrical Switching Frequency	(AC-1) 300 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 300 cycles per hour
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Mechanical Durability	5 million
Maximum Mechanical Switching Frequency	3600 cycles per hour

© 2024 ABB. All rights reserved.

Rated Control Circuit Voltage (U_c)	DC Operation 17 ... 32 V
Coil Consumption	Holding DC (Umin / Umax) 1.7 / 6.5 W Pull-in at Max. Rated Control Circuit Voltage DC 450 W Pull-in DC (Umin / Umax) 120 / 250 W
Operate Time	Between Coil De-energization and NC Contact Closing 8 ... 18 ms Between Coil De-energization and NO Contact Opening 5 ... 15 ms Between Coil Energization and NC Contact Opening 10 ... 27 ms Between Coil Energization and NO Contact Closing 30 ... 30 ms
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH75-25 (75 x 25 mm Mounting Rail) acc. to IEC 60715
Mounting by Screws (not supplied)	2 x M6 screws placed diagonally
Connecting Capacity Auxiliary Circuit	Solid 1 ... 4 mm²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP10 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Terminal Type	Ring-Tongue Terminals

Technical UL/CSA

General Use Rating UL/CSA	(600 V AC) 80 A
Horsepower Rating UL/CSA	(200 ... 208 V AC) Three Phase 15 hp (220 ... 240 V AC) Three Phase 20 hp (440 ... 480 V AC) Three Phase 40 hp (550 ... 600 V AC) Three Phase 50 hp

Environmental

Ambient Air Temperature	Close to Contactor without Thermal O/L Relay -40 ... 55 °C Close to Contactor without Thermal O/L Relay (Ucmin-Ucmax) according to IEC 60077 -40 ... +70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: B1 10 g Open, Shock Direction: B1 5 g Shock Direction: A 20 g Shock Direction: B2 15 g Shock Direction: C1 20 g Shock Direction: C2 20 g

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	CB_FR_701506-A1
CQC Certificate	CQC2018010304129269
Declaration of Conformity - CCC	2020980304001621
Declaration of Conformity - CE	1SBD250806U1000

© 2024 ABB. All rights reserved.

Declaration of Conformity - UKCA	1SBD250823U1000
EAC Certificate	EAC_RU C-FR ME77 B01010
GOST Certificate	GOST_POCCFRME77B07175

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	140 mm
Package Level 1 Depth / Length	146 mm
Package Level 1 Height	96 mm
Package Level 1 Gross Weight	1.2 kg
Package Level 1 EAN	3471522244710
Package Level 2 Units	box 20 piece
Package Level 2 Gross Weight	24 kg

Classifications

Object Classification Code	Q
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
ETIM 9	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → TAL and TAE Contactors → TAE50



© 2024 ABB. All rights reserved.