NEW

suzuka

S3 EN ISO 20345 : 2011 SRC - HRO

PRODUCT CHARACTERISTICS

HRO + 300°C (high heat-resistance)

EVA sole

ESD



- **FLEXIBLE**
- **SPORTY DESIGN**

2834 BLACK | POINTURE : 35 TO 48

COMPOSITION

Upper	Nubuck leather + Microfibre
Lining	3D mesh
Toe	Polycarbonate
Insole	Mesh over PU foam. Open cell.
Anti-puncture sole	Non-metallic
Sole	EVA inter / Nitrile rubber half-sole
Weight size 37*	470 g * Weight per shoe
Weight size 42*	562 g * Weight per shoe

**

Size 42 coefficient	Flat		Heel	
	Standard	Parade	Standard	Parade
SRA Anti-slip ceramic / Nals (soap solution)	0,32	0,43	0,28	0,51
SRB Anti-slip steel / Glycerine (oil)	0,18	0,18	0,13	0,15

SAFETY TABLE

	Safety toe (resistant to 200 joules)
P	Anti-puncture sole
SRC	Non-slip** sole
E	Shock-absorbent
A	Anti-static
FO	Hydrocarbon-resistant
WRU	Water-repellent upper

FACOM® brand and FACOM® logo are registered trademarks of Stanley Black & Decker Inc. or affiliated company and are used under licence.
Manufactured and distributed under licence by : Parade SAS

PARADE SAS • Route de Chaudron - St-Pierre-Montlimart - 49110 Montrevault-sur-Èvre • Tél. +33(0) 2 41 75 32 37 • Mail : contact@parade-protection.com
Parade reserves right to modify the product's manufacturing. ©Parade, All rights reserved. Non-contractual document. Update June 2022