JALHAKA SAS
00J0650

Softane™
Avant-Garde

S3 SRC
EN ISO 20345:2011
35 to 48

AP23
PLEINE FLEUR

0% METAL



- **Full grain AP 23 leather**
- **Softane™ dual-density sole**
- **Polymère toe cap type B and midsole no metallic**
- **Antistatic**

- Natural-coloured boot, fitted with two side tabs for easy pull-on.
- Bootstrap in full grain leather **AP 23**, water and oil resistant : a Jallatte exclusive
  - **10 to 15% thicker** (2.4mm) than most leathers usually used in safety shoe manufacture.
  - **Upper resistance to water penetration:** to European standard level or more.
- Flat binding at top of quarters.
- Two side tabs make them easy to pull on.
- Vamp lining in **3D** mesh, with honeycomb structure for improved all-round ventilation of the foot and fast-drying.
- **Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable.
- Ergonomic shoe with **broad synthetic polymer toe cap type B**, for saving on weight (50% lighter than steel) Impact resistance to **200 Joules.** Minimum height after test ≥ 4mm in relation to the Type A toe cap in accordance with Standard 22568-2:2019.
- New manufacturing process : antiperforation inner sole and insert in **FleXtane™ By Jallatte** material, antistatic, **100% composite**. Sewn directly onto the bootstrap and covering **100% of the foot** for all-round protection.
- **100% composite** materials : lighter than steel, non-magnetic, non-conductive of heat or cold.
- Heel stiffener to reinforce the heel seat.

- Dual-density **Softane™** sole with progressive heel shock absorber to protect back and joints from vibrations. Self cleaning sole pattern. Multi-directional treads. Rounded heel pressure zone for comfort and stability.

Slip resistance tests results
EN Standard : EN ISO 20345 : 2011
Requirement SRC (SRA+SRB)

SRA Test ground : ceramic/lubricant : water and detergent
On flat **0,38** (>0,32) – On the heel **0,30** (>0,28)

SRB Test ground steel/lubricant : glycerine
On flat **0,19** (>0,18) – On the heel: **0,14** (>0,13)

- Density of comfort layer = 0.45 / Density of wearing layer = 1.10
- Heel schock absorption 30 Joule
- Wrap-around profile for better stability when walking
- Highly resistant to oil and hydrocarbons
- Abrasion resistance 75 mm3
- Stainless steel midsole



Weight	Gross weight (42): 1532 g / Net weight (42): 1314 g
Size	35 to 48
Packaging	5 pairs
Box shoes (mm)	337 x 328 x 135
Cartons (mm)	625 x 425 x 345

Non contractual document
Copyright JALLATTE
Limited distribution

01/10/2021

Jallatte®
www.jallatte.com