Chemical protection

ALTO 260

Prolonged contact (or immersion) | intermittent wear

A good choice when dexterity and chemical protection is needed for extended wear



CHEMICAL PROTECTION
TYPE A

EN388
2120X

EN ISO 374-1
TYPE A
AKLMPT

EN ISO 374-5

CATEGORY 3

0334

DEXTERITY
EN420:
5/5

SPECIFIC ADVANTAGES

Comfort
- Added comfort and absorption of perspiration, due to the cotton flock-lining

Productivity
- Good grip on slippery objects, due to the embossed texture

Skin protection
- Good protection against chemical products

Guaranteed quality
- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Care for the environment
- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %

INDUSTRIES
- Chemical industry
- Aeronautics industry
- Other industries

APPLICATIONS
- Work with composite materials (resins)
- Common handling Tasks
- Resin and adhesive manufacturing
- Resin-working
- Maintenance in wet environments

Edit 28/11/2024

Chemical protection

ALTO 260

Prolonged contact (or immersion) | intermittent wear

LEGENDS

EN388



MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

2	1	2	0	X	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 2: Abrasion resistance

EN ISO 374-1



TYPE A

CHEMICAL RISKS

A: Methanol
K: Sodium hydroxide 40%
L: Sulphuric acid 96%
M: Nitric acid 65%
P: Hydrogen peroxide 30%
T: Formaldehyde 37%

EN ISO 374-5



MICRO-ORGANISMS

Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Flocked
Exterior finish	Embossed texture, chlorinated
Material	Natural latex
Cuff characteristic	Straight cuff
Colour.s	Black
Length (cm)	32
Thickness (mm)	0.8
European sizes	7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	2.2E+12 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	3.6E+12 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 10 pairs/bag 50 pairs/carton

LEGISLATION

- This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.
- This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1672
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 28/11/2024