Date: 11/04/2023

TR10-A, 1xPt100, 3-w, Cl.B, -50/500°C (F), Ø 6 mm, T15

TR10-A Measuring insert

Item number: 48803850

Quantity: 1 pcs.

Order code: TR10-A-ZZZZ-13DI-5L-037560R-Z-ZZ R1A 0375Z-Z-WIKA0-ZZ
T15.H-ZZZZZ-ZKK13C-M00050P00600-DZ000ZZ-ZZ A15
ZWIKA0W01SSZ

Overview:

TR10-A, 1xPt100, 3-w, Cl.B, -50/500°C (F), Ø 6 mm, T15

Diameter measuring insert: Ø 6 mm, 1.4571, l5=375 mm

Specifications according to data sheet: TE 60.01

T15.H, Ex: Without, customer spec. Pt100, 3w, -50...+600°C

Specifications according to data sheet: TE 15.01
Configuration sensor: Pt100
Output signal: 4 ... 20 mA, 2-wire-design
Tamb: Standard -40...85°C
Transmitter Signalling of error: Down scale 3,5 mA

Details:

TR10-A Measuring insert
Specifications according to data sheet: TE 60.01
1xPt100, 3-wire
Class B, IEC 60751
Temperature range of selected class: -50...+500°C
Transmitter: T15, Digital-transmitter, 4…20 mA, programmable
Measuring insert length [l5]: 375 mm
Diameter measuring insert: 6 mm
Sheath material measuring insert: Stainless steel 1.4571
Digital temperature transmitter for resistance sensors T15

Specifications according to data sheet: TE 15.01
Output signal: 4 ... 20 mA, 2-wire-design
Design: Head
Explosion protection: Without
Permissible ambient temperature transmitter: Standard -40...85°C
Configuration: Customer's specification
Configuration sensor: Pt100
Input configuration: 3-wire
Unit: °C
Measuring range start value - sign: Minus
Measuring range start value: 50

© 2023 - WIKA Instruments s.a.r.l.

Measuring range end value - sign: Plus (incl. 0)
Measuring range end value: 600
Transmitter Signalling of error: Down scale 3,5 mA

© 2023 - WIKA Instruments s.a.r.l.