Specifications

# Eaton 216377



## Catalog Number: 216377

Eaton Moeller® series M22 Contact element, Screw terminals, Front fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A M22-K10-GVP

### General specifications

**Product Name**
Eaton Moeller® series M22 Accessory Contact element

**Catalog Number**
216377

**EAN**
4015082163778

**Product Length/Depth**
38 mm

**Product Height**
10 mm

**Product Width**
32 mm

**Product Weight**
0.01 kg

**Compliances**
CE

Powering Business Worldwide

## Features & Functions

Electric connection type

Screw connection

## General

Model

Top mounting and integrable

Mounting method

Front fastening

## Climatic environmental conditions

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

70 °C

Ambient storage temperature - min

-25 °C

Ambient storage temperature - max

85 °C

## Electrical rating

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V

6 A

Rated operational current (Ie) at DC-13, 500 V

0.1 A

## Contacts

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

0

Number of contacts (normally open contacts)

1

## Resources

Catalogs

eaton-rmq-titan-brochure-br047004en-en-us.pdf

eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

Flip catalog - Product Range Catalog - Command and indication

Certification reports

000Z425

Declarations of conformity

DA-DC-00004971.pdf

DA-DC-00004141.pdf

DA-DC-00004975.pdf

DA-DC-00004180.pdf

DA-DC-00004134.pdf

DA-DC-00004135.pdf

DA-DC-00004157.pdf

DA-DC-00004176.pdf

### Drawings

eaton-operating-actuation-m22-led-element-dimensions.eps

eaton-general-standards-000Z425.jpg

eaton-operating-contact-m22-contact-element-3d-drawing-004.eps

eaton-operating-adapter-m22-contact-element-flow-diagram.eps

eaton-operating-devices-adapter-flow-diagram-002.eps

### eCAD model

ETN.216377.edz

### Installation instructions

IL04716002Z

### Installation videos

RMQ Flat Design

### mCAD model

DA-CD-kontaktelement_schraube_front

DA-CS-kontaktelement_schraube_front

### Multimedia

MCI Multicolor Light Indicator M22 with SmartWire-DT

MCI MultiColor Light Indicator RMQ compact solution

RMQ small E-Stop emergency-stop button

easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator

### Sales notes

eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf

eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf

eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf

eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf

### System overview

Pilot devices - selection aid

### Wiring diagrams

eaton-operating-contact-m22-contact-element-wiring-diagram-002.eps




Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia