Specifications

Eaton 216381

Catalog Number: 216381

Eaton Moeller® series M22 Contact element, Screw terminals, Base fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A M22-KC10-GVP



General specifications

Product Name
Eaton Moeller® series M22 Accessory Contact element

Catalog Number
216381

EAN
4015082163815

Product Length/Depth
38 mm

Product Height
32 mm

Product Width
10 mm

Product Weight
0.01 kg

Compliances
CE Marked

Certifications
IEC 60947-5
CSA Std. C22.2 No. 14-05
UL 508
CSA Std. C22.2 No. 94-91
EN 60947-5

Catalog Notes
1 N/C contact box mounting

Powering Business Worldwide

Features & Functions

Color

Green

Electric connection type

Screw connection

General

Model

Top mounting

Mounting method

Floor fastening

Climatic environmental conditions

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

70 °C

Ambient storage temperature - min

-25 °C

Ambient storage temperature - max

85 °C

Electrical rating

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V

6 A

Rated operational current (Ie) at DC-13, 500 V

0.1 A

Contacts

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

0

Number of contacts (normally open contacts)

1

Resources

Catalogs

eaton-rmq-titan-brochure-br047004en-en-us.pdf

Flip catalog - Product Range Catalog - Command and indication

eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

Certification reports

000Z425

Declarations of conformity

DA-DC-00004141.pdf

DA-DC-00004134.pdf

DA-DC-00004975.pdf

DA-DC-00004180.pdf

DA-DC-00004971.pdf

DA-DC-00004135.pdf

DA-DC-00004176.pdf

DA-DC-00004157.pdf

Drawings

eaton-operating-pushbutton-m22-dimensions-003.eps

eaton-operating-contact-m22-contact-element-3d-drawing-003.eps

eaton-general-standards-000Z425.jpg

eaton-operating-adapter-m22-contact-element-flow-diagram-003.eps

eCAD model

ETN.216381.edz

Installation instructions

IL04716002Z

Installation videos

RMQ Flat Design

mCAD model

DA-CD-kontaktelement_schraube_boden

DA-CS-kontaktelement_schraube_boden

Multimedia

easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator

MCI Multicolor Light Indicator M22 with SmartWire-DT

RMQ small E-Stop emergency-stop button

MCI MultiColor Light Indicator RMQ compact solution

Sales notes

eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf

eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf

eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf

eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf

System overview

Pilot devices - selection aid

Wiring diagrams

eaton-operating-contact-m22-contact-element-wiring-diagram-002.eps



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia