



jalas® 3438 ARIOSO

EN ISO 20345:2022 S1, PL, FO

Learn more

Safety sandal, nail protection material plasma-treated composite (PTC) textile, toecap material aluminium, plastic shank, PU outsole, upper material PU-coated leather;Textile

CHARACTERISTICS

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Breathable
- Good shock absorption

FUNCTIONS

- ProNose toe reinforcement
- Oil-resistant outsole
- Anti-static properties
- Low weight
- Polstered shaft edge
- Ventilating insole
- Conforms with IEC 61340-5-1 (ESD)
- Rear shock absorption zone

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE

Indoors, environments with risk for outsole penetration

SPECIFICATION

TYPE Safety footwear, Sandals
CATEGORY Cat. II
NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile
FITTING Regular
UPPER MATERIAL PU-coated leather, Textile
PRONOSE MATERIAL PU
TOECAP MATERIAL Aluminium
LINING MATERIAL Polyester, polyamide
INSOLE FX1 Classic
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Shock absorption zone in Ergothan
OUTSOLE MATERIAL PU outsole
FASTENING Hook-and-loop
COLOUR Black
NET WEIGHT, (SIZE 42) 1.07 kg

COMPLIANCE

CE Cat. II

EAC TP TC 019:2011

EN ISO 20345:2022 S1, PL, FO

ÖNORM Z 1259

DGUV 112-191

FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- ESD
- Aluminium toecap
- Oil-resistant outsole
- ProNose toe reinforcement
- Nail protection in plasma-treated composite (PTC) textile

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
36	3	4	5	3438-36	6408487435409
37	4	5	6	3438-37	6408487435416
38	5	5½	6½	3438-38	6408487435423
39	6	6½	7½	3438-39	6408487435430
40	6½	7½	8½	3438-40	6408487435447
41	7	8	9	3438-41	6408487435454
42	8	9	10	3438-42	6408487435461
43	9	9½	11	3438-43	6408487435478
44	10	10½	11½	3438-44	6408487435485
45	10½	11	12½	3438-45	6408487435492
46	11	12	13	3438-46	6408487435508
47	12	13	14	3438-47	6408487435515

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.