StarTech.com
Hard-to-find made easy®

Data Sheet

# 1m External Mini SAS Cable - Serial Attached SCSI SFF-8088 to SFF-8088

Product ID: ISAS88881



The ISAS88881 1m External SAS Cable is designed for high-performance networks, servers, workstations and desktops, supporting data transfer rates of up to 6 Gbps.

This durable Mini SAS cable features SFF-8088 to SFF-8088 plugs for connecting your external SAS devices (controllers, hard drives, SAN storage area network, etc.), and it is TAA-compliant for Federal (GSA Schedule) purchases.

Constructed of high quality materials this 1-meter SAS cable is backed by StarTech.com's Lifetime Warranty.

## Certifications, Reports and Compatibility

RoHS & REACH DOWNLOAD DECLARATION

TAA COMPLIANT

## Applications

- For use in Storage Area Networks, to connect SAS Expander enabled controllers and enclosures
- Connect SAS Controllers to SAS Backplanes
- Connect external hard drive to SAS Controller

## Features

- 2x SFF-8088 plugs with latches
- Durable metal connectors
- Supports data transfer rates up to 6 Gbps
- Multi-lane design
- Backwards compatible with SATA devices

| | | |
|---|---|---|
| | Warranty | Lifetime |
| **Hardware** | Cable Jacket Type | PVC - Polyvinyl Chloride |
| | Cable Shield Type | Aluminum-polyester foil with tinned copper braid |
| | Number of Conductors | 8 Twisted Pair |
| **Connector(s)** | Connector A | 1 - SFF-8088 (26-pin, External Mini-SAS) Latching Plug |
| | Connector B | 1 - SFF-8088 (26-pin, External Mini-SAS) Latching Plug |
| **Physical Characteristics** | Cable Length | 3.3 ft [1 m] |
| | Color | Black |
| | Product Length | 3.3 ft [1 m] |
| | Weight of Product | 5 oz [143 g] |
| | Wire Gauge | 28 AWG |
| **Packaging Information** | Package Height | 0.6 in [14 mm] |
| | Package Length | 13 in [33 cm] |
| | Package Quantity | 1 |
| | Package Width | 9.8 in [25 cm] |
| | Shipping (Package) Weight | 5.7 oz [161 g] |
| **What's in the Box** | Included in Package | 1 - 1m External Serial Attached SCSI SAS Cable - SFF-8088 to SFF-8088 |

Product appearance and specifications are subject to change without notice.