NEW

ravira

S1P EN ISO 20345: 2011 SRC
HRO

PRODUCT CHARACTERISTICS

- HRO — High resistance to heat and tearing
- Non-magnetic
- EVA sole for maximum comfort

The+ PARADE TECHNOLOGIES

- VPS SYSTEM — Supports the arch of the foot



7760 GREY AND LILAC | SIZE: 36 TO 42

COMPOSITION

Upper	Fabric and Split leather
Linning	3D Mesh
Toe Cap	Composite
Stay clean insole	Mesh over PU foam. Removable.
Puncture proof insert	Non-metallic
Sole	Rubber / EVA
Weight for size 37*	410g * Weight per shoe

SAFETY TABLE

- Toe cap (200J)
- P — Antipuncture sole
- SRC — Antislip sole **
- E — Shock-absorption
- A — Antistatic
- FO — Oil and fuel resistant shoe

**

Size coefficient 42	Flat		Heel	
	Standard	Parade	Standard	Parade
SRA ceramic floor / Nals (soap solution)	0,32	0,45	0,28	0,41
SRB Steel / Glycerine (oil)	0,18	0,20	0,13	0,18

PARADE SAS • Route de Chaudron - St-Pierre-Montlimart - 49110 Montrevault-sur-Èvre - France • Ph. +33(0) 2 41 75 32 37 • Mail: contact@parade-protection.com
Parade reserves the right to modify the product's manufacturing. ©Parade, All rights reserved. Non-contractual document. Update March 2020