Cut protection

KRYTECH 643

Moderate risk - ISO C

Comfort, Suppleness & breathability without any compromise on cut protection & durability
Can be used with touch devices & touch screen



RESICOMFORT TECHNOLOGY

CUT PROTECTION
LEVEL C

EN388	EN407	CAT.2
4X42C	X1XXXX	CE

ISO 13997:	DEXTERITY
13,5 N	EN 420: 5/5

OEKO-TEX® CONFIDENCE IN TEXTILES
STANDARD 100
CQ 979/2 IFTH
Tested for harmful substances.
www.oeko-tex.com/standard100

SPECIFIC ADVANTAGES

Comfort
- A seamless plaited glove for a maximum comfort, dexterity and flexibility while providing optimal cut protection (Cut level ISO C)

Durability
- Extended use guaranteed by our exclusive process RESICOMFORT. Proven breathability, flexibility and durability of the coating.

Skin protection
- Free of harmful substances: STANDARD 100 by OEKO-TEX®, DMF Free
- Dermatologically approved

Suitable for touchscreen
- Can be used with touch devices & touch screen

Guaranteed quality
- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Washability
- Washable 1 time at 40°C without any alteration on performances*.

Practical
- Cut level easy to identify thanks to the marking on the back of the glove.

INDUSTRIES
- Automotive/mechanical industry
- Glass industry
- Manufacturing
- Industrial maintenance
- White appliance

APPLICATIONS
- Handling glass sheets
- Maintenance with cut risk
- Metal working
- Assembly of small parts
- Assembly of thin metal sheets
- Automotive assembly
- Bodywork assembly
- Finishing sharp parts
- Handling and sorting small, sharp parts

Edit 16/03/2022

Cut protection

KRYTECH 643

Moderate risk - ISO C

LEGENDS

EN388 MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

4	X	4	2	C	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 1: Contact heat resistance
- X: Limited flame spread

PRODUCT DETAILS

Interior finish	Seamless textile support from HDPE fibres
Gauge	15
Exterior finish	Reinforced grip
Material	Nitrile foam sandy
Cuff characteristic	Knitted Cuff
Colour.s	Black Grey
Size	6 7 8 9 10 11

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag 48 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/10/20/2586
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

* Tests carried out on unworn gloves (i.e. in new condition) which differs from the reality in the field.

Edit 16/03/2022