DATASHEET - LS-XOR

Actuating rod

Part no. LS-XOR
290190

EL Number (Norway) 4356169

Product name	Eaton Moeller® series LS Accessory Actuating rod
Part no.	LS-XOR
EAN	4015082901905
Product Length/Depth	25 millimetre
Product height	120 millimetre
Product width	25 millimetre
Product weight	0.035 kilogram
Compliances	Contact Manufacturer
Certifications	CSA IEC/EN 60947-5 UL 508 CSA-C22.2 No. 14 UL CE UL Category Control No.: NKCR UL File No.: E29184 CSA Class No.: 3211-03 CSA File No.: 012528
Product Tradename	LS
Product Type	Accessory
Product Sub Type	Actuating rod
Catalog Notes	Do not use together with LS…-CC basic device.
Features	The operating head can be rotated 90° to enable adaptation to the specified approach direction
Product category	Actuating rod
Type	Operating heads
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Actuator type	Without actuator
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Please enquire
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Sensors (EG000026) / Drive head for position switches/hinge switches (EC001483)			
Electric engineering, automation, process control engineering / Binary sensor technology, safety-related sensor technology / Position switch / Drive head for position switches (ecl@ss10.0.1-27-27-06-04 [BAA083012])			
Type of control element			Without actuator

© 04/2023 by Eaton Industries GmbH