Specifications

Eaton 265544

Catalog Number: 265544

Eaton Distribution parts. Impulse relay, 48AC/24DC, 1W, 16A, 50Hz, 1SU



General specifications

Product Name	**Catalog Number**
Eaton Distribution parts	265544
EAN	**Product Length/Depth**
4015082655440	80 mm
Product Height	**Product Width**
70 mm	17.5 mm
Product Weight	**Compliances**
0.136 kg	RoHS conform

Powering Business Worldwide

Product specifications

Mounting method

DIN rail

Control voltage 1 type

AC

Ambient operating temperature - max

45 °C

Ambient operating temperature - min

-20 °C

Control voltage 1 - max

48 V

Control voltage 1 - min

48 V

Control voltage 2 - max

24 V

Control voltage 2 - min

24 V

Frequency control voltage 1 - max

50 Hz

Frequency control voltage 1 - min

50 Hz

Frequency control voltage 2 - max

50 Hz

Frequency control voltage 2 - min

50 Hz

Heat dissipation per pole, current-dependent

1.5 W

Incandescent lamp load - max

0 W

Load fluorescent lamp - max

0 VA

Load fluorescent lamp (duo circuit) - max

0 VA

Load fluorescent lamp (parallel compensated) - max

0 VA

Number of contacts (change-over contacts)

Resources

Declarations of conformity

DA-DC-03_Z-S

DA-DC-03_Z-S_SC_SB

Drawings

eaton-dimensions-mas-z-s230.jpg

eaton-3d-drawing-z-s230-scha2.jpg

eaton-wiring-diagram-z-s-1te.jpg

1

Number of contacts (normally closed contacts)

0

Number of contacts (normally open contacts)

0

Rated operational current for specified heat dissipation (In)

16 A

Rated switch current

16 A

Equipment heat dissipation, current-dependent

1.5 W

Supply voltage - max

250 V

Supply voltage - min

250 V

Switching current (cos phi = 0.6) - max

0 A

Width in number of modular spacings

1

Built-in depth

60 mm

Operating mode

Manual operation possible

Control voltage 2 type

DC

Voltage type

AC

Functions

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia