PILZ
THE SPIRIT OF SAFETY

PIT en1.0a-5m-s 401111



Enabling switch, 3 levels, 1 signal contact, 6-core cable (5 m) with open end.

Technical details

General data	
Approval:	CE
Self-monitored:	no
Technical data	
Relay outputs	
Utilisation cat. AC15/DC13sta.:	EN 60947-5-1
Voltage AC15 safety cont.:	125 V
Max. current AC15 safety cont.:	0.3 A
Voltage DC13 safety cont.:	30 V
Max.current DC12 safety cont.:	1 A
Environmental data	
Ambient temperature:	0 - 50 °C
Mechanical data	
Length cable:	5 m
Material of cable insulation 1:	PUR
Mounting position:	any
Connection type:	5 m cable
Housing material lower section:	PP
Height dimension:	125 mm
Width dimension:	45 mm

Depth dimension:	45 mm
Diameter:	45 mm
Net weight:	361 g
Gross weight:	388 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	no
REACh compliance:	Contains no SVHC substances
WEEE classifikation (08/2018):	5 devices (feed size < 50cm)
Commercial data	
Harmonized System Code:	85371098
UNSPSC 25:	32131023
EAN-Code:	4046548065145
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27371238
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC002571
Volume:	0 dm3