Date: 11/04/2023

LF-1; 0...50 inWC gauge; 4 … 20 mA (pressure) + HART, 2-wire

Submersible pressure sensor for superior applications

Item number:	48795100
Quantity:	1 pcs.
Order code:	LF-1FAEGB-NG212-4DA-AM0010Z2BZZ-ZZZZZZ-Z W101ALF1Z-AA1CHPL3LF
Overview:	LF-1; 0...50 inWC gauge; 4 … 20 mA (pressure) + HART, 2-wire @ DC 12...30 V; 1.0% of span;-10...+50°C; 10 meter PUR ;1.4404 / 316L ; FM Gas Class I, Division 1 4...20 mA-Standard(press): U+ brown, U- blue; Shield-grey Test protocol: with test protocol Specifications according to data sheet: LM 40.04
Details:	Submersible pressure sensor for superior applications

Specifications according to data sheet: LM 40.04
Measuring range: 0...50 inWC gauge
Output signal: 4 … 20 mA (pressure) + HART, 2-wire
Power supply: DC 12...30 V
Accuracy: 1.0% of span
Cable material: PUR
Unit cable length: meter
Cable length: 10
Case material: 1.4404 / 316L
Approval: FM
Atmosphere: Gas Class I, Division 1
Permissible medium temperature: -10...+50°C
Test protocol: with test protocol
Pin assignment: 4...20 mA-Standard(press): U+ brown, U- blue; Shield-grey
shield: connected
Customer logo: WIKA standard
Customer address: WIKA Alexander Wiegand SE & Co. KG 63911 Klingenberg
Model name customer-specific: LF-1

© 2023 - WIKA Instruments s.a.r.l.