Date: 11/04/2023

S5551/4, NS160, 0...160°C, L1=140 x6mm

Bimetal thermometer, stainless steel version

Item number: 48764668

Quantity: 1 pcs.

Order code: S5551 -4-C1K-ND-B140H1Z-AHAZZZZ TB UZZZEZSVID-AZ1ZZZZZ1ZZZZ

Overview:
S5551/4, NS160, 0...160°C, L1=140 x6mm
Process connection: 1/2 NPT
laminated safety glass, liquid damping
Explosion protection: ATEX Case: 316SS
Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X)
WIKA Serial number *...*

Details:
Bimetal thermometer, stainless steel version
Specifications according to data sheet: TM 55.01
Case: stainless steel
Stem material: stainless steel
Model: S 5551, nominal size 160, adjustable stem and dial
Accuracy class: class 1 per EN 13190
Connection design: 4, compression fitting, sliding on stem
Unit: °C
Scale range: 0 °C ... 160 °C
Process connection: 1/2 NPT
Stem diameter: 6 mm
Insertion length L1: 140 mm
Window: laminated safety glass
Damping: liquid damping
Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X)
Case: 316SS
Version: standard
Stem material: stainless steel
Ingress protection: IP 65
Permissible ambient temperature: -40 ... +70 °C
Manufacturer logo: *WIKA*
serial number on dial: Serial number *...*
Explosion protection: ATEX
Ignition protection type: Ex h

© 2023 - WIKA Instruments s.a.r.l.