



jalas® TEMPUS 5668

EN ISO 20345:2011 S1, P, SRC ASTM F2413-18 M/I/C SD 35 PR ASTM F3445-21 SR

Learn more

COMFORTABLE SAFETY SHOE WITH BOA FIT SYSTEM

Ventilated, sporty, and comfortable safety shoe with green details and advanced shock absorption with PORON XRD, BOA® Fit System, protective toe cap and flexible nail penetration insert made of textile material. The well proven outsole has a very effective grip pattern and is made of a special nitrile rubber for high durability. The JALAS® Tempus shoes are ESD and antistatic certified to be used in ESD protected work environments.

CHARACTERISTICS

- Excellent shock absorption
- Perfect fit
- Extra comfortable
- Very breathable
- Extremely light
- Excellent grip

FUNCTIONS

- Oil-resistant outsole
- Anti-static properties
- Ventilating insole
- Low weight
- Bellows tongue
- Conforms with IEC 61340-5-1 (ESD)
- BOA® Fit System
- Double shock absorption zones
- Ergonomically shaped
- Soft

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic, slipping

PRIMARY ENVIRONMENTS OF USE

Indoors, environments with risk for outsole penetration, dry environments, clean environments

SPECIFICATION

TYPE Safety footwear, Low shoes
CATEGORY Cat. II
NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile
FITTING Narrow/Regular
COLLECTION Tempus
UPPER MATERIAL Microfiber, Textile
TOECAP MATERIAL Steel
LINING MATERIAL Polyester, polyamide
INSOLE FX2 Pro Slim
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in Poron® XRD®
MIDSOLE MATERIAL EVA
OUTSOLE MATERIAL Nitrile rubber outsole
FASTENING BOA® Fit System
COLOUR Black, Green, White
NET WEIGHT, (SIZE 42) 0.96 kg

COMPLIANCE

CE Cat. II

EAC TP TC 019:2011

Information/UIS

EN ISO 20345:2011
S1, P, SRC

ASTM F2413-18
M/I/C
SD 35 PR

ASTM F3445-21
SR

ÖNORM Z 1259

DGUV 112-191

FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- ESD
- Oil-resistant outsole
- Steel toecap
- Nail protection in plasma-treated composite (PTC) textile

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	3½	4	5668-35	6408487542732
36	3	4	5	5668-36	6408487542787
37	4	5	6	5668-37	6408487542831
38	5	5½	6½	5668-38	6408487542886
39	6	6½	7½	5668-39	6408487542930
40	6½	7½	8½	5668-40	6408487542985
41	7	8	9	5668-41	6408487543036
42	8	9	10	5668-42	6408487543081
43	9	9½	11	5668-43	6408487543135
44	10	10½	11½	5668-44	6408487543180
45	10½	11	12½	5668-45	6408487543234
46	11	12	13	5668-46	6408487543289
47	12	13	14	5668-47	6408487543333
48	13	13½	14½	5668-48	6408487543388

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.