Specifications

Eaton 730-32026-00P



Catalog Number: 730-32026-00P

Eaton DG1 Mounting frame, For use with: DG1 (frame size FS5)
DXG-ACC-FR5N12FK

General specifications

Product Name	**Catalog Number**
Eaton DXG Mounting frame	730-32026-00P
EAN	**Product Length/Depth**
4015081721610	55 mm
Product Height	**Product Width**
845 mm	105 mm
Product Weight	**Compliances**
2.609 kg	CE

Powering Business Worldwide

Product specifications

Used with

DG1

Product Category

Accessories

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Resources

Catalogs

Product Range Catalog Drives Engineering

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

Declarations of conformity

DA-DC-00004130.pdf

DA-DC-00003384.pdf

Drawings

eaton-regulating-equipment-options-dg1-mounting-frame-3d-drawing.eps

Manuals and user guides

MN040002_EN

mCAD model

DA-CS-dg1_fs5_f

DA-CD-dg1_fs5_f

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Fitted with:

Fixing screws
Frame parts

Accessory/spare part type

Flange

Ambient operating temperature - max

50 °C

Ambient operating temperature - min

-10 °C

Functions

For the power section's push-through installation outside the control panel



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia