TILLA™

Safety spectacle. Single piece polycarbonate frame suitable for over-spectacle use.

SPECIAL FEATURES

- Can be worn over spectacles
- Adjustable and inclinable temples
- Ventilated temple tips and side shields
- Brow protection
- Anti-scratch and Anti-fog lens
- UV400 protection
- Ideal to be worn by site visitors



VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	RLY00461	2C-1.2 ℮ 1FT CE / Z87+ U6	℮ EN 166 FT CE / Z87+	Impacts, UV radiations	Riley Anti-scratch and Anti-fog
GREY	RLY00462	5-2.5 ℮ 1FT CE	℮ EN 166 FT CE	Impacts, UV and Solar radiations	

See overleaf for this product's technical specification ····►

TILLA™

GENERAL SPECIFICATION

LENS BASE	2mm
WEIGHT	42g

PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS AND NOSE BRIDGE	Polycarbonate	Single piece, moulded with side protection
TEMPLE	Polycarbonate / Thermoplastic Elastomers (TPE)	Co-injected - Flexible and comfortable
HINGE	Metal	Durable

LENS MARKINGS (CE)

LENS FILTER TYPE:
2C UV
5 Solar

SCALE NUMBER (SHADE):
1.2 Clear or Amber
2.5 Grey

Identity of the manufacturer

OPTICAL CLASS:
1 High optical quality

MECHANICAL STRENGTH:
F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
T Protection against high-speed particles at extreme temperatures

CE Certification mark

FRAME MARKINGS

Identity of manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:
F Low energy impact, resists a 6mm, 0.86 g ball at 45m/s
T Protection against high-speed particles at extreme temperatures

CE Certification mark

USA (ANSI)

LENS
U6 UV (Clear, Amber, Blue)
L1.7 Solar (I/O, Twilight)
L2.5 Solar (Grey)

LENS AND FRAME:
Z87+ High velocity impact, 0.25 inch, 1.04g ball at 150ft/s

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.
MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.
STORAGE: All products must be stored in a dry and clean environment.

PART OF THE GLOBUS GROUP

Based on a substantial heritage of successfully protecting hands, Globus has grown to become one of the world leaders in worker safety, leading the way in technical innovation to provide a range of products that have set the standard for safety, productivity and wearer acceptance.

This focus on creating cutting edge personal protection solutions has now extended to eye and face protection with Riley; a new collection of high performance protective eyewear products engineered with innovation and ingenuity, designed for optimum comfort and styled for safe working.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

www.riley-eyewear.com
E: info@riley-eyewear.com
T: +44 (0)161 877 4747
F: +44(0)161 877 4746
Globus (Shetland) Ltd, 14 Central Park, Mosley Road, Manchester, M17 1NY, UNITED KINGDOM

EC-Type certification issued by:
0194: INSPEC, 56 Leslie Hough Way, Salford, Greater Manchester, M6 6AJ, United Kingdom
The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment.
The manufacturer reserves the right to make any modifications it deems necessary.

© 2018 Globus (Shetland) Ltd | RILEY-DATA-TILLA-0419