Specifications

Eaton 187253



Catalog Number: 187253

Eaton Moeller series xPole - AFDD+ Arc Fault Detection Device, 2 poles, B13A, 30mA, type F

General specifications

Product Name	**Catalog Number**
Eaton Moeller series xPole - AFDD+ Arc fault detection device	187253
	EAN
	4015081823024
Product Length/Depth	**Product Height**
80 mm	73 mm
Product Width	**Product Weight**
52.5 mm	0.277 kg
Compliances	**Certifications**
RoHS conform	CE

Powering Business Worldwide

Delivery program

Application
Switchgear for residential and commercial applications

Product range
AFDD

Basic function
Arc fault circuit interrupter

Product application
Switchgear for residential and commercial applications

Number of poles
Two-pole

Release characteristic
B

Tripping characteristic
B

Rated current
13 A

Rated current of product range
10-40 Ampere

Fault current rating
0.03 A

Sensitivity type
Type F

Pulse-current sensitive up to 1 kHz and ≤10 mA smooth DC current

Type
AFDD+

Technical data - electrical

Voltage rating
230 V

Current test marks
As per inscription

Impulse withstand current
Surge-proof, 3 kA

Frequency
50 Hz

Leakage current type
A

Rated switching capacity (IEC/EN 61009)
10 kA

Rated short-circuit breaking capacity
10 Kilo Ampere

Rated short-circuit breaking capacity (EN 60947-2)
0 kA

Rated short-circuit breaking capacity (EN 61009)
10 kA

Test circuit AC
170 - 264 Voltage AC

Tripping
Short time-delayed

Control voltage type auxiliary equipment
AC

Rated voltage auxiliary device
230 V

Rated switch current auxiliary device
0 A

Overvoltage category
III

Pollution degree
2

Lifespan, electrical
4000 operations

Technical data - mechanical

Frame

45 mm

Width In Number Of Modular Spacings

3

Built-in width

54 mm

Device height

80 mm

Built-in depth

67 mm

Mounting style

Tri-stable slide catch - enables removal from existing busbar combination

Degree of protection

IP20

Degree of protection (built in)

IP40

Terminals (top and bottom)

Twin-purpose

Terminal protection

Busbar tag shroud as per VBG4, ÖVE-EN 6

Permissible Storage and Trans Temp. Min

-35 °C

Permissible Storage and Trans Temp. Max

60 °C

Contact position indicator

red / green

Thickness of busbar material

0.8 - 2 Square Millimeter

Climatic proofing

IEC/EN 61009

Lifespan, mechanical

20000 operations

Design verification as per IEC/EN 61439 - technical data

Rated operational current for specified heat dissipation (In)

13 A

Equipment heat dissipation, current-dependent

6 W

Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be

evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Additional information

Current limiting class

3

Additional equipment attached at delivery

Fire protection switch

Types conform to

IEC/EN 61009

IEC/EN 62606

Resources

Brochures

eaton-afdd-guidance-brochure-br003010en-en-us.pdf

Catalogs

eaton-2020-es-emea-uk-pdd-catalogue-update-july-2020.pdf

Characteristic curve

eaton-xpole-afdd-characteristic-curve.jpg

eaton-xpole-afdd-characteristic-curve-002.jpg

Declarations of conformity

DA-DC-03_AFDD

03_AFDD-F_310820

DA-DC-03_AFDD-F

Drawings

eaton-xpole-afdd-dimensions.jpg

eaton-xpole-afdd-3d-drawing-003.jpg

eaton-xpole-afdd-3d-drawing.jpg

Installation instructions

IL019125ZU

Installation videos

Arc Fault Detection Device - AFDD+

Technical data sheets

eaton-afdd-catalog-tech-en-us.pdf

Wiring diagrams

eaton-xpole-afdd-wiring-diagram.jpg



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia