TEGERA®



A soft, comfortable, and heat resistant (up to 250° C/482° F) natural latex glove with perfect grip.

TEGERA® 8160

Learn more

PROTECTS AGAINST WET AND CONTACT HEAT

A soft, comfortable, and heat resistant (up to 250° C/482° F) 0,5 mm/19,6 mil natural latex glove with perfect grip thanks to a foam pattern. Suitable for work in areas where there is a risk of contact heat injuries. Flexible chemical protection glove for allround work.

CHARACTERISTICS

- Comfortable
- High level of protection
- Good grip
- Flexible

FUNCTIONS

- Waterproof
- Withstands contact heat up to 250°C

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Heat injuries, contact with dirt, contact with moisture, contact with damp

PRIMARY ENVIRONMENTS OF USE

Slippery environments, warm environments, wet environments, moist environments, dirty environments

PRIMARY AREAS OF USE

Agricultural work, building and construction, cleaning, concrete work, decontamination, hot work, marine work, paint spraying work, painting, paper industry work, petro-chemical work, sanitation, wood industry work

PRIMARY INDUSTRIES OF USE

Agriculture, pulp and paper, building and construction

TYPE OF WORK

Medium weight

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION

TYPE All-round work gloves, Chemical protection gloves, Heat protection gloves
CATEGORY Cat. III
THICKNESS 0,5* mm (*chem-layer)
LINING MATERIAL Interlock
LENGTH 300 mm
GRIP DESIGN Foam grip pattern
COLOUR Blue
PAIRS PER: BUNDLE/CARTON 12/120
DISPLAY TYPE Bulk pack
DIPPING Double-dipped, Fully dipped
DIPPING MATERIAL Latex
INNER MATERIAL SPECIFICATION Cotton
OUTER MATERIAL SPECIFICATION Natural latex

COMPLIANCE

CE 0598

UKCA Cat. III

EAC

TP TC 019:2011

Information/UIS

LATEX

EN ISO 374-1:2016/A1:2018 Type B AKLPT

EN ISO 374-5:2016

EN 407:2020 (No flame protection) X2XXXX

EN 388:2016+A1:2018 3131X

EN ISO 21420:2020

FEATURES

Windproof

Waterproof

Chemical protection

TEST ACCORDING TO EN ISO 374-1:2016

Tested chemical	A	K	L	P	T
Permeation level	2	2	3	5	6
Degradation %	-2,8	-7,7	55,7	-4,6	-21,9

SIZE		ARTICLE NUMBER	EAN
6	XS	8160-6	7392626008038
7	S	8160-7	7392626007543
8	M	8160-8	7392626007550
9	L	8160-9	7392626007567
10	XL	8160-10	7392626007574
11	XXL	8160-11	7392626007581

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.