Geberit Mapress Carbon Steel bend (FKM, blue)



Example image



APPLICATION PURPOSES

- For district heating water ≤ 140 °C
- For thermal media (solar)
- For mineral and lubricating oil
- For motor fuels (e.g. diesel)
- For compressed air (oil purity class 3–4)
- For solar technology, industry and shipbuilding

CHARACTERISTICS

- Pressing indicator
- Outside zinc-plated
- Seal ring made of FKM, blue
- Pressing socket with black protection plug

TECHNICAL DATA

Product material	Non-alloy steel 1.0034 E195 (EN 10305)

INFO

- Dimension changes of individual articles as per table will be completed by end of May 2026

Art. no.	DN	d, ø mm	arc °	L cm	Z cm
51222	12	15	45	3.6	1.6
51223	15	18	45	3.7	1.7
51224	20	22	45	4.2	2.1
51225	25	28	45	4.8	2.5

Art. no.	DN	d, ø mm	arc °	L cm	Z cm
51226	32	35	45	4.3	1.7
51227	40	42	45	5.1	2.1
51228	50	54	45	6.2	2.7
51231	65	76.1	45	10.3	5
51232	80	88.9	45	11.7	5.7
51233	100	108	45	14.3	6.8
51282	12	15	90	4.9	2.9
51283	15	18	90	5.3	3.3
51284	20	22	90	6.1	4
51285	25	28	90	7.2	4.9
51286	32	35	90	6.8	4.2
51287	40	42	90	8	5
51288	50	54	90	10	6.5

Art. no.	DN	d, ø mm	arc °	L cm	Z cm
51291	65	76.1	90	15.7	10.4
51292	80	88.9	90	18.4	12.4
51293	100	108	90	22.6	15.1