NEW

ELIGHT

SB EN ISO 20345 : 2022 SB SR FO PS WPA CI HI E
ASTM F2413-18 M I C EH PR

2022 STANDARD VERSION



■ **1824 BLACK** | 35 ▶ 48

PRODUCT CHARACTERISTICS

- FO — Hydrocarbon resistance
- CI — Insulated sole (cold)
- HI — Insulated sole (heat)
- Non-magnetic

PARADE TECHNOLOGIES

- VPS SYSTEM — Supports the arch of the foot
- DRS SYSTEM — Shock-absorbent
- Be flex 2.0 — Extra-flexible sole

• SHOE WITH INSULATING SOLE PROVIDING PROTECTION FROM RISKS OF ELECTRIC SHOCKS IN DRY ENVIRONEMENT

ASTM 2413-18
1000V AC - 1500 V DC

Combinaison of 3 insulating elements
- **Vibram® nitrile rubber half sole**
- **APT insulating sole**
- **insulating insole**

COMPOSITION

Upper	Leather
Front reinforcement	Injected PU
Lining	3D Mesh
Toe	Composite
Insole	Mesh over PU foam. Removable. Insulating
Anti-puncture sole	Insulating fabric
Sole	Two-density polyurethane (insulating)
Weight size 42*	625 g *Weight per shoe

**

Size coefficient 42	front		heel	
	Standard	Parade	Standard	Parade
Ceramic floor / Nals (soap solution)	0,36	**0,36**	0,31	**0,31**
SR Ceramic floor + glycerine	0,22	**0,22**	0,19	**0,19**

SAFETY TABLE

EN ISO 20345 : 2022 SB SR FO PS WPA CI HI E

- Toe protection *(Safety toe cap)*
- Slip-resistance** *Ceramic flooring + detergent*
- SR — Slip-resistance ** *(ceramic flooring + oil)*
- FO — Hydrocarbon resistance
- PS — Puncture-resistance *Non-metallic insert PS = Small spike 3mm*
- CI — Sole insulation (cold)
- HI — Sole insulation (heat)
- E — Energy-absorbing heel
- WPA — Water-repellent upper

ASTM F2413-18 M I C EH PR

- EH — Electric insulation *in dry environments*

Parade reserves the right to modify the product's manufacturing characteristics. ©Parade, All rights reserved. Non-contractual document. Updated 10/2024