Warning Beacons





NEW

- Modern design
- Simple mounting
- High protection rating IP 65 – suitable for indoor and outdoor use

Technical specifications:

Housing:

ABS/PC-Blend

Cap:

Polycarbonate, transparent

Fixing:

Base, bracket or
tube mounting*

Socket:

B 15 d, BA 15 s

Terminal:

Screw free clamp mechanism for
2 x 0.75 mm² to 2 x 1.5 mm²
Outer diameter 7 - 11 mm
Protection rating to VDE specifications

Duty cycle:

100 % max. 10 W

Bulb not included in assembly

(* Base 975 840 90 must be ordered twice for base mounting – once as socket for beacon and once as base.)

Order specifications:

Order No.	
826 ☐ 00 00	Signal beacon, 12 - 240 V ≅ BA 15 d (available 04/98)
826 ☐ 20 00	Signal beacon, 24 V ≅ BA 15 s

▲
1 = red 3 = yellow

Please state colour code.

Special parts:

975 826 01	Bracket for wall mounting
975 845 10	Tube ø 25 mm, 100 mm long Aluminium anodized
975 840 90	Base for tube (order double)

Bulb BA 15 d, 42 mm
955 826 35 24 V, 10 Watt
955 826 38 230 V, 10 Watt
Bulb BA 15 s, 52 mm
955 021 35 24 V, 21 Watt





