PRODUCT-DETAILS

# E1.2C 630 Ekip Dip LSI 4p F F

## E1.2C 630 Ekip Dip LSI 4p F F



### General Information

| | |
|---|---|
| Extended Product Type | E1.2C 630 Ekip Dip LSI 4p F F |
| Product ID | 1SDA071342R1 |
| EAN | 8015644751920 |
| Catalog Description | E1.2C 630 Ekip Dip LSI 4p F F |
| Long Description | C.BREAKER SACE EMAX2 E1.2C 630 FIXED FOUR-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP/DIP-LSI R 630 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED |

### Ordering

| | |
|---|---|
| EAN | 8015644751920 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |
| Order Code US and Canada | ZACNEEBB000A000000XX |

### Dimensions

| | |
|---|---|
| Product Net Width | 280 mm |
| Product Net Height | 296 mm |
| Product Net Depth / Length | 183 mm |
| Product Net Weight | 16 kg |

## Container Information

| | |
|---|---|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 350 mm |
| Package Level 1 Height | 350 mm |
| Package Level 1 Depth / Length | 330 mm |
| Package Level 1 Gross Weight | 18 kg |
| Package Level 1 EAN | 8015644751920 |

## Environmental

| | |
|---|---|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

## Additional Information

| | |
|---|---|
| Current Type | AC |
| Electrical Durability | Ue =< 440 V 8000 cycle<br>Ue = 500 ... 690 V 8000 cycle<br>30 cycles per hour |
| Mechanical Durability | 20000 cycle<br>60 cycles per hour |
| Neutral Pole Current ([% Iu]) | 100 % |
| Number of Poles | 4 |
| Power Loss | 31 W |
| Product Main Type | SACE Emax 2 |
| Product Name | Air Circuit Breaker |
| Product Type | Air Circuit Breaker |
| Rated Service Short-Circuit Breaking Capacity, in % of Icu ($I_{cs}$) | 100 % |
| Rated Current ($I_n$) | 630 A |
| Rated Voltage ($U_r$) | 690 V |
| Rated Impulse Withstand Voltage ($U_{imp}$) | acc. to IEC 60947-2 12 kV |
| Rated Insulation Voltage ($U_i$) | AC 1000 V |
| Rated Operational Voltage | 690 V AC |
| Rated Service Short-Circuit Breaking Capacity ($I_{cs}$) | (220 V AC) 50 kA<br>(230 V AC) 50 kA<br>(380 V AC) 50 kA<br>(400 V AC) 50 kA<br>(415 V AC) 50 kA<br>(440 V AC) 50 kA<br>(500 V AC) 42 kA<br>(660 V AC) 42 kA<br>(690 V AC) 42 kA |
| Rated Short-time Withstand Current Low Voltage ($I_{cw}$) | for 1 s 42 kA<br>for 3 s 24 kA |
| Rated Ultimate Short-Circuit Breaking Capacity ($I_{cu}$) | (400 V AC) 50 kA<br>(415 V AC) 50 kA<br>(440 V AC) 50 kA<br>(500 V AC) 42 kA<br>(525 V AC) 42 kA<br>(690 V AC) 42 kA |
| Rated Uninterrupted Current ($I_u$) | 630 A |
| Release | Ekip Dip LSI |

| | |
|---|---|
| Release Type | EL |
| Short-Circuit Performance Level | C |
| Standards | IEC |
| Sub-type | E1.2 |
| Terminal Connection Type | Front |
| Version | F |

## Certificates and Declarations (Document Number)

| | |
|---|---|
| Data Sheet, Technical Information | 1SDC200023D0209 |
| Declaration of Conformity - CE | 9AKK106713A5546 |
| Environmental Information | 9AKK10103A1038 |
| Instructions and Manuals | 1SDH000999R0002 |
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |

## Classifications

| | |
|---|---|
| ETIM 4 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 5 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 6 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 7 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

## Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

