Date: 11/04/2023

SC15.30.060 0 ... 150°C/°F UL CL.2

Tension thermometer - Indicating temperature controller SC15

Item number:	7821502
Quantity:	1 pcs.
Order code:	SC15-UZ30060AZ20DLO4AAZZZZZZZZC0150Z19V0600070G4Z5 ZZZZZ125ZZZZZZZ#A2EZ
Overview:	SC15.30.060 0 ... 150°C/°F UL CL.2 standard, plastic case Panel mounting with clamp, with protective cap IP54 1 adjustable changeover switch, adjusting knob with key Stop, fixed: 125 °C 5 A non-inductive at max. 250VAC 50/60Hz terminal block Capillary [FL]: 1.50 m Copper double copper braided, 2x Supportspirales (sensor - case) Connection design: SV19 G1/2B Insertion length [L1] o. [U1]: 70 x 6 mm Stainless Steel Dial background: black *10890376-11* UL Certificate
Details:	Tension thermometer - Indicating temperature controller SC15 Specifications according to data sheet: TV 28.02 Model: SC15 - combistat UL Approval: UL Certificate Design: standard, plastic case Nominal size [NG, d1]: 60 mm Mounting option: Panel mounting with clamp, Ingress protection [IP]: with protective cap IP54 Unit: Double scale °C/°F Scale range: 0 ... 150°C/°F Contact type: 1 adjustable changeover switch, Contact adjustment: adjusting knob with key Switch rating: 5 A non-inductive at max. 250VAC 50/60Hz Cable connection: terminal block Capillary material: Copper double copper braided, Capillary [FL]: 1.50 Connection design: SF91/SV19 - Connection rotatable with lose connection, Probe material: Stainless Steel Probe diameter [d5] o. [F1]: 6 mm Insertion length [L1] o. [U1]: 70 Process connection [d6 o. E]: Male thread G1/2B

© 2023 - WIKA Instruments s.a.r.l.

Stop, fixed: 125
Accuracy class: class 2 per EN 13190
Capillary protection: 2x Supportspirales (sensor - case)
individual text: *10890376-11*
Dial background: black

© 2023 - WIKA Instruments s.a.r.l.