
Product data sheet

LLTHC 30 U T0 P5

Slim-line carriage, standard length, standard height





Size:	30
W1 [mm]:	60
N [mm]:	16
H [mm]:	42
H2 [mm]:	11.3
H3 [mm]:	9
L1 [mm]:	100.4
L2 [mm]:	67.4
L3 [mm]:	40
L4 [mm]:	14.6
W3 [mm]:	40

Date: 19/02/2019

® SKF is a registered trademark of the SKF Group.
© SKF 2010
The contents of this report are the copyright of the publisher and may not be reproduced (even extracts) unless permission is granted. Every care has been taken to ensure the accuracy of the information contained in this report but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

Product data sheet

LLTHC 30 U T0 P5

Slim-line carriage, standard length, standard height

H4 [mm]:	8.5
H5 [mm]:	8
D3 [mm]:	
S2:	M8
W [mm]:	28
H1 [mm]:	26
H6 [mm]:	13.8
F [mm]:	80
D1 [mm]:	9
D2 [mm]:	14
Emin [mm]:	12
Emax [mm]:	70
Lmax [mm]:	3944
Weight [kg]:	0.81
Weight [kg/m]:	4.8
C [N]:	26100
C0 [N]:	41900
Mx[Nm]:	329
Mx0[Nm]:	528
M y/z[Nm]:	256
M y0/z0[Nm]:	410
Preload class:	Zero preload T0
Precision class:	Standard P5

Date: 19/02/2019

® SKF is a registered trademark of the SKF Group.
© SKF 2010
The contents of this report are the copyright of the publisher and may not be reproduced (even extracts) unless permission is granted. Every care has been taken to ensure the accuracy of the information contained in this report but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.