CAT. N° 4 062 80



UNDERVOLTAGE RELEASE DX³ - 24 TO 48 V~/= -TIME DELAY ADJUSTABLE FROM 0 TO 300 MS

Pack (number of units)	1
Volume (dm³)	0,219
Weight (g)	83,00

Product characteristics

Remote tripping auxiliaries

- To fit on the left-hand side of DX³ and TX³ devices
- Maximum 1 remote tripping auxiliary per device
- Allow insertion of the supply busbar
- No tool required for joining together the auxiliary and the main device.
- For MCBs, RCBOs, RCCBs and remote trip isolating switches

Undervoltage releases

- For remote tripping of its associated device in case of mains voltage drop down or with the help of a N/C push button
- 24 to 48 V~/=
- Number of modules : 1

General characteristics

Signalling, remote tripping auxiliaries and motorised controls DX³

Documentation

Catalogue pages & additional information

- Description page (p.072)
- Dimensions of din-rail equipment

Installation & technical data

- F01224EN-01

Installation instructions & related documents

- G3363J

Environmental product profile

- Environnemental product sheet n°8 E0095A-FR
- LGRP-01267-V01

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.