SCHAEFFLER



FAG

X-life

7214-B-XL-TVP

Angular contact ball bearing

Schaeffler ID:
0167254250000

Angular contact ball bearing 72..-B-XL-TVP, single row, X-life, plastic cage

Technical information





Main Dimensions & Performance Data

d	70 mm	Bore diameter
D	125 mm	Outside diameter
B	24 mm	Width
C_r	74,000 N	Basic dynamic load rating, radial
C_{0r}	62,000 N	Basic static load rating, radial
C_{ur}	4,300 N	Fatigue load limit, radial
n_G	7,200 1/min	Limiting speed
$n_{\vartheta r}$	5,400 1/min	Reference speed
	1.09 kg	Weight

Mounting dimensions

$d_{a\ min}$	79 mm	Minimum diameter of shaft shoulder
$D_{a\ max}$	116 mm	Maximum diameter of housing shoulder
$D_{b\ max}$	119.4 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	1.5 mm	Maximum fillet radius of shaft
$r_{a1\ max}$	1 mm	Maximum fillet radius of housing

Dimensions

r_{min}	1.5 mm	Minimum chamfer dimension
$r_{1\ min}$	1 mm	Minimum chamfer dimension
D_1	104 mm	Shoulder diameter on outer ring wide side face
d_1	92.3 mm	Shoulder diameter on inner ring wide side face
a	53 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product. For further information you can use the contact form on our website.

SCHAEFFLER

Temperature range		
T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product. For further information you can use the contact form on our website.