Cut protection

KRYTECH 809

Low risk - ISO B



CUT PROTECTION
LEVEL B

EN388



4X42B

CAT.CATEGORY 2

CE

ISO 13997:

9.5 N

DEXTERITY

EN 420:
5/5

OEKO TEX®
STANDARD 100
CQ 979/2
IFTH

Level B cut resistant gloves with crotch reinforcement. Enhanced durability combined with a high suppleness thanks to the HDPE liner. Touchscreen ability.

SPECIFIC ADVANTAGES

Comfort

- Added comfort and flexibility
- Ergonomic to reduce fatigue in the hand

Durability

- Suitable for long-term wear : excellent abrasion resistance
- A reinforced crotch in nitrile for an improved durability for the most exposed areas

Skin protection

- Contains traces of DMF in compliance with occupational exposure limits
- Free of harmful substances: STANDARD 100 by OEKO-TEX®

Suitable for touchscreen

- Can be used with touch devices & touch screen (thumb & index)

Washability

- Washable up to 5 times at 40°C without any alteration on performances* allowing to extend glove lifespan, reduce costs and waste.

INDUSTRIES

- Automotive/mechanical industry
- Aeronautics industry
- Construction Industry (Carpenters/Joiners)
- Construction Industry (Roofers/Tilers/Glazers)
- Construction Industry (Heating engineers/Plumbers)
- Construction Industry (Metalworkers/Locksmiths)
- Transport, logistics
- Paper industry
- Industrial equipment / Metal transformation
- White appliance

APPLICATIONS

- Assembly of thin metal sheets
- Automotive assembly
- Handling and sorting small, sharp parts
- Precision assembly
- Installing steel structures
- Assembly
- Laying tiles, inserts, frames or zinc sheeting
- Handling metal parts
- Goods handling on loading bays, docks, warehousing etc.
- Operating handling equipment

Edit 08/08/2023

Cut protection

KRYTECH 809

Low risk - ISO B

LEGENDS

EN388



MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

4	X	4	2	B	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 4: Abrasion resistance

PRODUCT DETAILS

Interior finish	Seamless textile support from HDPE fibres
Gauge	13
Exterior finish	Ventilated back
Material	Polyurethane
Cuff characteristic	Knitted Cuff
Colour.s	Black
Length (cm)	21-27
European sizes	5 6 7 8 9 10 11

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag 48 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/01/22/0144
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

* Tests carried out on unworn gloves (i.e. in new condition) which differs from the reality in the field.

Edit 08/08/2023