NEW

n-fuze

S3 EN ISO 20345: 2011 SRC
HRO - CI - HI

PRODUCT CHARACTERISTICS

- HRO — High resistance to heat and tearing
- CI-HI — Insulation against hot and cold
- Non-magnetic
- Offset heel
- Wide fit

The + PARADE TECHNOLOGIES

- VPS SYSTEM — Supports the arch of the foot





QUICK VELCRO OPENING

■ 3854 BLACK | SIZE: 36 TO 48

COMPOSITION

Upper	Coated split leather
Linning	3D Mesh
Toe Cap	Composite
Stay clean insole	Fabric over EVA foam. Removable.
Puncture proof insert	Non-metallic
Sole	Rubber / PU
Weight for size 42*	744g * Weight per shoe

**

Size coefficient 42	Flat		Heel	
	Standard	Parade	Standard	Parade
SRA ceramic floor / Nals (soap solution)	0,32	0,61	0,28	0,67
SRB Steel / Glycerine (oil)	0,18	0,19	0,13	0,18

SAFETY TABLE

- Toe cap (200J)
- P — Antipuncture sole
- SRC — Antislip sole **
- E — Shock-absorption
- A — Antistatic
- FO — Oil and fuel resistant shoe
- WRU — Water-repellent upper

PARADE SAS • Route de Chaudron - St-Pierre-Montlimart - 49110 Montrevault-sur-Èvre - France • Ph. +33(0) 2 41 75 32 37 • Mail: contact@parade-protection.com
Parade reserves the right to modify the product's manufacturing. ©Parade, All rights reserved. Non-contractual document. Update March 2020