Specifications

Eaton 125078

Catalog Number: 125078

Eaton SPX System bus adapter with CANopen interface; can be plugged into variable frequency drive SPX



General specifications

Product Name
Eaton SPX system bus adapter

Catalog Number
125078

EAN
4015081226894

Product Length/Depth
39 mm

Product Height
6 mm

Product Width
22 mm

Product Weight
0.2 kg

Certifications
IEC/EN61800-5
CSA-C22.2 No. 14
IEC/EN61800-3
UL 508C
Certified by UL for use in Canada
UL
UL Category Control No.: NMMS, NMMS2, NMMS7. NMMS8
UL File No.: E134360
CE
UL report applies to both US and Canada

Catalog Notes
The expansion module is plugged into the variable-frequency drive.

Powering Business Worldwide

General

Product Category

Accessories

Suitable for

Branch circuits, (UL/CSA)

Type

System bus adapter with CANopen® interface

Design verification

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Application notes

Connecting drives to generator supplies

SPI - Variable frequency drives with a common DC bus

Electromagnetic compatibility (EMC)

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00004868.pdf

DA-DC-00004869.pdf

DA-DC-00004871.pdf

DA-DC-00004866.pdf

Drawings

eaton-regulating-equipment-options-spx-output-expansion-3d-drawing.eps

Installation instructions

IL04012011Z2021_04.pdf

Multimedia

Eaton variable frequency drives - Demand more than good enough

Eaton variable frequency drives - Demand more innovation

Eaton variable frequency drives - Demand more expertise

How does a VFD work to save energy and money?

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia