Cut protection

KRYTECH 600

Low risk - ISO B

Cut, Grip and Skin protection for very oily environments



GRIP & PROOF TECHNOLOGY

CUT PROTECTION
LEVEL B

EN388	EN407	
4X42B	X1XXXX	ISO 18889
CATEGORY 3	ISO 13997:	DEXTERITY
CE 0334	6 N	EN ISO 21420: 5/5

OEKO TEX® STANDARD 100 CQ 979/3 IFTH

SPECIFIC ADVANTAGES

Comfort
- Unbeatable fingertip sensitivity

Durability
- Excellent abrasion resistance due to the nitrile coating

Productivity
- Grip and Proof coating ensures an excellent grip in oily environment. It also reduces muscle strain and boost productivity

Skin protection
- Free of harmful substances: OEKO-TEX® STANDARD 100, DMF Free
- Oilproof, it repels oil penetration and reduce dermatitis

Guaranteed quality
- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Care for the environment
- 95 gr CO_2 of carbon footprint reduction (1)
- Recycled material in the glove: 20 %
- Recycled material in the liner: 37 %
- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %

INDUSTRIES
- Automotive/mechanical industry
- Mechanical industry
- Other industries

APPLICATIONS
- Cutting and stamping metal
- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Precision assembly
- Glass working
- Machine maintenance
- Maintenance in wet environments
- Bodywork assembly
- Handling and sorting small, sharp parts
- Handling oily mechanical parts
- Machining parts using cutting oil

Edit 04/12/2024

Cut protection

KRYTECH 600

Low risk - ISO B

LEGENDS

EN388 MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

4	X	4	2	B	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 THERMAL RISKS (HEAT AND FIRE)

PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- 0-4: Limited flame spread

PROTECTION FROM PESTICIDES

GR: Re-entry tasks

ISO 18889

PRODUCT DETAILS

Interior finish	Seamless textile support from HDPE fibres
Gauge	13
Exterior finish	Fully-coated
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colour.s	Black Grey
European sizes	7 8 9 10

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag 48 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/01/19/0175 ext 02/01/19 updated 03-08/12/2023
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

(1) Measurement based on life cycle analysis, carried out by Glimpact, an independent third party, according to the European PEF method adopted by European Commission, based a pair of Grip&Proof cut B nitrile gloves.

Edit 04/12/2024