LOWWIND S3 Vibram®

Ci Hi Hro SRC 0% METAL

Standard EN ISO 20345 : 2011

LEMAITRE
Safety since 1974





Sizes 35 to 49 Réf. **LOWWS30BFVA**

Product Highlights

- **All-terrain shoe available with men's and women fit.**
- **2,0 mm thick high strengh leather** (against abrasion, tearing and puncture). Tongue with gusset to avoid any infiltration of dust / stones.
- **Reinforced front of the shoe and anti-abrasion scuffcap** for an extended life span over time.
- **Anatomical and anti-bacterial Energy+ insock:** reduce feeling of fatigue, odor neutralization.
- **Protective toe-cap**: HDFC composite.
- **Puncture-resistant midsole:** high tenacity fabric "0" penetration



TRAIL VIBRAM® PU/nitrile rubber antistatic sole

Vibram

- **Exclusive technical sole developed in partnership with Vibram®.**
- **Outdoor sole** with excellent grip, Hi, HRO, suitable for harsh weather conditions (hot and cold).
- **Excellent resistance to abrasion.**
- **Dropped heel (15 mm high)** for improved safety, especially on ladders.

USE

- Construction trades, road maintenance, networks, green spaces and outdoor activities.

FRENCH TRADEMARK

DEVELOPED RESPECTING THE FOOT ANATOMY

lemaitre-securite.com

Lemaitre takes care.

LOWWIND S3 Vibram®

Ci Hi Hro △ SRC [0% METAL]

Standard EN ISO 20345 : 2011

VARIANT



Freewind S3 SRC
FREWS30BFVA

Characteristics of the upper

- **Upper:** water-repellent leather and reinforced anti-abrasion scuffcap
- **Tongue with gusset:** high tenacity textile
- **Lining:** 3D micro-prorous fabric

Practical information

Women's fitting 35-39	**Men's fitting** 40-49
Weight of one shoe size 38 : 575 g	Weight of one shoe size 42: 740 g
AET N° 0075/007/161/05/16/0555 EXT 06/09/16	**AET N°** 0075/007/161/05/16/0555 EXT 01/05/16

Characteristics of the sole

- **Designation:** TRAIL VIBRAM®
- **Material:** polyurethane / nitrile rubber - Vibram® antistatic
- **Antistatic sole**
- **SRA Adhesion coefficient:**
  forward flat slip: 0,32 (standard ≥ 0,32)
  forward heel slip: 0,35 (standard ≥ 0,28)
- **SRB Adhesion coefficient:**
  forward flat slip: 0,20 (standard ≥ 0,18)
  forward heel slip: 0,17 (standard ≥ 0,13)

Packaging

shoebox	355 x 220 x 130 mm
carton	660 x 450 x 360 mm
	10 shoeboxes per carton

Gencods

35	3237154066355	**43**	3237154066430
36	3237154066362	**44**	3237154066447
37	3237154066379	**45**	3237154066454
38	3237154066386	**46**	3237154066461
39	3237154066393	**47**	3237154066478
40	3237154066409	**48**	3237154066485
41	3237154066416	**49**	3237154066492
42	3237154066423		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear			
SBP			
S1			A E Fo
S1P			A E Fo
S2			A E Fo Wru
S3			A E Fo Wru

200 J toe-cap: protection of the forefoot against impact and crushing.

Anti-perforation insert 1100 N: foot protection against perforation.

- A — Anti-static footwear
- E — Shock absorption at the heel
- Fo — Fuel oil-resistant outsole
- Wru — Water penetration and water absorption resistant upper
- ESD — Electrostatic discharge
- Ci — Insulation against cold
- Hi — Insulation against heat
- Hro — Outsole resistance to hot contact
- Wr — Water resistant
- An — Ankle protection

△ SRA — Slip-resistance on ceramic floors with detergent

△ SRB — Slip-resistance on steel floors with glycerol

△ SRC = △ SRA + △ SRB

Lemaitre Sécurité
17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com

LEMAITRE
Safety since 1974

DON_LS 04 TDS 0178
update: 15/04/24

Member of SYNAMAP

afaq ISO 9001 Qualité AFNOR CERTIFICATION

afaq ISO 14001 Environnement AFNOR CERTIFICATION