Date: 11/04/2023

F73.100/1, 0...200°C, L1=80 mmx8mm,

Gas actuated thermometer, stainless steel series

Item number:	48781705
Quantity:	1 pcs.
Order code:	F73.100-C1L-1BK-C0080-N03-1-Z-HZZ-AHAZZZ G7 FZZZEVZZIWS-AZ1ZZZZZ2ZZZZ
Overview:	F73.100/1, 0...200°C, L1=80 mmx8mm, plain, without thread radial bottom Surface mounting flange, stainless steel standard capillary stainless steel 1.4571 Capillary length: 3 m laminated safety glass Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) class 1 per EN 13190 *WIKA* with Serial number
Details:	Gas actuated thermometer, stainless steel series Specifications according to data sheet: TM 73.01 Case: stainless steel Stem material: stainless steel Model: F73.100, nominal size 100, with capillary Unit: °C Scale range: 0 °C ... 200 °C Connection design: 1, plain stem Process connection: plain, without thread Stem diameter: 8 mm Insertion length L1: 80 mm Capillary: standard capillary stainless steel 1.4571 Capillary length: 3 m Design of case mounting: Surface mounting flange, stainless steel Explosion protection: ATEX Ignition protection type: Ex h Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) Accuracy class: class 1 per EN 13190 Ingress protection: IP 65 Window: laminated safety glass Case: Stainless steel Connector location: radial bottom Manufacturer logo: *WIKA* Permissible ambient temperature: -40 … +60 °C with Serial number

© 2023 - WIKA Instruments s.a.r.l.