Specifications

# Eaton 9701-6005-00P

## Catalog Number: 9701-6005-00P

Eaton DG1 Variable frequency drive, 230 V AC, 3-phase, 248 A, 75 kW, IP21/NEMA1, Brake chopper, DC link choke



### General specifications

**Product Name**
Eaton DG1 variable frequency drive

**Catalog Number**
9701-6005-00P

**EAN**
4015081805839

**Product Length/Depth**
371 mm

**Product Height**
1035 mm

**Product Width**
486 mm

**Product Weight**
109 kg

**Certifications**
C-Tick
Certified by UL for use in Canada
IEC/EN61800-3
UkrSEPRO
Safety requirements: IEC/EN 61800-5
UL File No.: E134360
RoHS, ISO 9001
CE
CSA-C22.2 No. 274-13
UL508
UL Category Control No.: NMMS, NMMS7
UL
Specification for general requirements: IEC/EN 61800-2
UL report applies to both US and Canada
IEC/EN 61800-3
EAC
CUL
IEC/EN61800-5

Powering Business Worldwide

Catalog Notes

## Features & Functions

### Features

Temperature-controlled fan

Externally accessible fan

Parameterization: Fieldbus

Parameterization: Keypad

Parameterization: Power Xpert inControl

### Functions

4-quadrant operation possible

## General

### Air volume capacity

739 m³/h

### Cable length

200 m, screened, maximum permissible, Motor feeder

C2 ≤ 10 m, Radio interference level, maximum motor cable length

C3 ≤ 50 m, Radio interference level, maximum motor cable length

### Degree of protection

IP21

NEMA 1

### Electromagnetic compatibility

1st and 2nd environments (according to EN 61800-3)

### Environmental class

3C2, 3S2 (Air quality)

### Fitted with:

Internal DC link

Control unit

DC link choke

Radio interference suppression filter

Multi-line graphic display

Brake chopper

Breaking resistance

PC connection

Additional PCB protection

IGBT inverter

### Frame size

FS6

### Mounting position

Vertical

### Number of slots

2 (expansion)

### Overvoltage category

III

### Pollution degree

2

### Product Category

Variable frequency drives

### Protection

Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)

### Radio interference class

C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.
C1: with external filter, for conducted emissions only
Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments

### Safety function/level

STO (Safe Torque Off, SIL1, PLc Cat 1)

### Shock resistance

UPS drop test (for weights inside the UPS frame)
Storage and transportation: maximum 15 g, 11 ms (inside the packaging)
Mechanical, According to EN 61800-5-1, IEC/EN 60068-2-27

### Suitable for

Branch circuits, (UL/CSA)

### Vibration

Resistance: 5 - 15.8 Hz, Amplitude 1 mm (peak)
Resistance: 5 - 150 Hz, According to EN 61800-5-1, IEC/EN 60068-2-6
Resistance: 15.8 – 150 Hz, 1 g, Maximum acceleration amplitude

## Climatic environmental conditions

### Altitude

Max. 1000 m
Max. 2000 m for Corner Grounded TN Systems
Max. 3000 m
Above 1000 m with 1 % derating per 100 m

### Ambient operating temperature - min

-10 °C

### Ambient operating temperature - max

50 °C

### Ambient operating temperature at 150% overload - min

-30 °C

### Ambient operating temperature at 150% overload - max

50 °C

### Ambient storage temperature - min

-40 °C

### Ambient storage temperature - max

70 °C

### Climatic proofing

< 95 average relative humidity (RH), no condensation, no corrosion

## Main circuit

### Current limitation

0.1 - 2 x IH (CT), motor, main circuit

### Efficiency

97.5 % ( η)

### Heat dissipation at current/speed

1128 W at 100% current and 50% speed
1287 W at 50% current and 50% speed
1417 W at 50% current and 90% speed
1955 W at 100% current and 0% speed
2377 W at 50% current and 0% speed
2686 W at 100% current and 90% speed
845 W at 25% current and 0% speed
951 W at 25% current and 50% speed

### Input current ILN at 110% overload

290.3 A

Input current ILN at 150% overload

241.4 A

Leakage current at ground IPE - max

7.2 mA

Mains current distortion

26 %

Mains switch-on frequency

Maximum of one time every 60 seconds

Mains voltage - min

208 V

Mains voltage - max

240 V

Operating mode

Torque regulation

U/f control

Sensorless vector control (SLV)

Speed control with slip compensation

Output frequency - min

0 Hz

Output frequency - max

400 Hz

Output voltage (U2)

240 V AC, 3-phase

230 V AC, 3-phase

Overload current IL at 110% overload

343.2 A

Overload current IL at 150% overload

372 A

Rated conditional short-circuit current (Iq)

100 kA

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

45 Hz

Rated frequency - max

66 Hz

Rated operational current (Ie) at 110% overload

312 A

## Motor rating

Assigned motor current IM at 220 - 240 V, 60 Hz, 150% overload

192 A

Assigned motor current IM at 230 V, 50 Hz, 110% overload

279 A

Assigned motor current IM at 230 V, 50 Hz, 150% overload

233 A

Assigned motor current IM at 230 V, 60 Hz, 110% overload

248 A

Assigned motor power at 230/240 V, 60 Hz, 1-phase

100 HP

Assigned motor power at 230/240 V, 60 Hz, 3-phase, 110 % overload

125 HP

## Apparent power

Apparent power at 230 V

124.3 kVA

Apparent power at 240 V

129.7 kVA

## Braking function

Braking resistance

1.4 Ω

Braking torque

Adjustable to 150 %, DC - Main circuit

Adjustable to 150 % (I/Ie), DC - Main circuit

Max. 100 % of rated operational current Ie with external braking resistor - Main circuit

Max. 30 % MN, Standard - Main circuit

Switch-on threshold for the braking transistor

425 VDC

## Control circuit

Number of inputs (analog)

2

Rated operational current (Ie) at 150% overload

248 A

Rated operational power at 220/230 V, 50 Hz, 1-phase

75 kW

Rated operational power at 220/230 V, 50 Hz, 3-phase, 110% overload

90 kW

Rated operational voltage

230 V AC, 3-phase

240 V AC, 3-phase

Resolution

0.01 Hz (Frequency resolution, setpoint value)

Short-circuit protection rating

400 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring

Starting current - max

200 %, IH, max. starting current (High Overload), For 2 seconds every 20 seconds, Power section

Supply frequency

50/60 Hz

Switching frequency

2 kHz, 1 - 10 kHz adjustable, fPWM, Power section, Main circuit

System configuration type

TN-S, TN-C, TN-C-S, TT, IT

Voltage rating - max

240 VAC

Number of inputs (digital)

8

Number of outputs (analog)

2

Number of outputs (digital)

1

Number of relay outputs

3 (parameterizable, 2 changeover contacts and 1 N/O, 6 A (240 V AC) / 6 A (24 V DC))

Rated control voltage (Uc)

24 V DC (external, max. 250 mA options incl.)

## Communication

Communication interface

Ethernet IP, built in

DeviceNet, optional

SmartWire-DT, optional

PROFIBUS, optional

Modbus RTU, built in

Modbus TCP, built in

BACnet MS/TP, built in

CANopen®, optional

Connection to SmartWire-DT

Yes

In conjunction with DXG-NET-SWD SmartWire DT module

Protocol

TCP/IP

Other bus systems

MODBUS

PROFINET IO

DeviceNet

PROFIBUS

CAN

BACnet

EtherNet/IP

## Design verification

Equipment heat dissipation, current-dependent Pvid

2736 W

Heat dissipation capacity Pdiss

## Resources

Application notes

Torque control

Starting, stopping and operation

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Rated operational current for specified heat dissipation (In)

248 A

Static heat dissipation, non-current-dependent Pvs

59.17 W

Heat dissipation details

Operation (with 150 % overload), allow for derating

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

Electromagnetic compatibility (EMC)

PID controller

DG1 in pump and fan applications

Digital I/Os

Real time clock and use of the timers

Motor data and V/f curves

Operating at low temperatures

Dual Rating What exactly does that mean?

Connecting drives to generator supplies

Smoke Mode and fire mode

Load balancing in multi motor applications

Analog I/Os

## Catalogs

Product Range Catalog Drives Engineering

## Declarations of conformity

DA-DC-00004676

DA-DC-00004620.pdf

## eCAD model

DA-CE-ETN.DG1-32248FB-C21C

## Manuals and user guides

MN040002_EN

## mCAD model

DA-CD-dg1_fs6_mit

DA-CS-icpd_dg1_fr6_mit

## Multimedia

PowerXL DG1 Variable Frequency Drive - Setup via WebUI

Power XL General Purpose Drives

## Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf

### 10.8 Connections for external conductors

Is the panel builder's responsibility.

### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.



© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.