
MIKALOR

W1 Spring Clip





Spring clips are designed to distribute pressure uniformly around the application zone, thanks to the material used in their manufacture

Their use is recommended when the hose is subject to rapid changes in temperature which can cause expansion and contraction of the materials used in the assembly.

These clips are quick and easy to assemble and can even be mounted manually in some cases, without the need for tools.

MATERIAL:	C67S W1 Steel
FINISH:	Zinc-plated Cr3
CORROSION RESISTANCE:	144 hours Salt Spray (ASTM B-117)

Ø d1	Part Number	Ø di ±0.2	b +1 -0.2	a ±0.5	S	Box Quantity	Outer Box Quantity
6	02014025	5,5	7	3,0	0.5	500	8.000
7	02014033	6,4	7	3,0	0.5	500	8.000
8	02014041	7,4	8	3,0	0.6	500	8.000
9	02014050	8,4	8	3,5	0.6	500	4.000
10	02014068	9,3	8	3,5	0.7	500	4.000
11	02014076	10,3	8	4,0	0.7	500	4.000
12	02014084	11,1	8	4,0	0.7	500	4.000
14	02014092	12,9	8	4,0	0.8	500	4.000
15	02014105	13,5	8	5,2	0.8	500	4.000
17	02014113	15,3	8	5,0	0.8	500	4.000
20	02014121	18,0 ±0.4	8	4,2	0.8	500	4.000