TEGERA®





TEGERA® INFINITY 8810

Learn more

SUPER SOFT WINTER GLOVE, PALM DIPPED

Winter lined glove with super soft nitrile foam palm dipping for the cold season or in cool work areas. Designed for versatile work in dry to semi-dry environments. It is warm and comfortable but still soft and flexible with the high dexterity and fingertip sensitivity that is unique for an Infinity glove. Breathable materials for all day comfort. Skin friendly with Derma-test and Oeko-Tex certificate.

CHARACTERISTICS

- Durable
- Extra comfortable
- Good fingertip sensitivity
- Flexible
- Warm
- Good grip

FUNCTIONS

- Withstands contact heat up to 100°C
- Approved for handling foodstuffs

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping, contact with cold

PRIMARY ENVIRONMENTS OF USE

Dry environments, cold environments, moist environments, dirty environments

PRIMARY AREAS OF USE

Machine operating, building and construction, carpentry, installation work, construction, transport work, machine driving, warehouse work, airport work, repair work

PRIMARY INDUSTRIES OF USE

Machinery and equipment, mro, transportation, utilities, building and construction, logistics

TYPE OF WORK

Medium weight

SPECIFICATION

TYPE Cold insulation gloves, Heat protection gloves
CATEGORY Cat. II
COLLECTION Infinity
LINING Winter-lined
LINING MATERIAL Fleece, Nylon, Acrylic, Spandex, 10 gg, 15 gg
LENGTH 235-275 mm
DEXTERITY 5
GRIP DESIGN Foam grip pattern
COLOUR Black, Yellow
PAIRS PER: BUNDLE/CARTON 6/120
DISPLAY TYPE Bulk pack
DIPPING Palm-dipped
DIPPING MATERIAL Nitrile foam, Waterbased PU
CUFF STYLE Knitwrist cuff
CUFF MATERIAL Textile
CUT RESISTANCE (EN ISO 13997) TDM: 8 N
INNER MATERIAL SPECIFICATION Acrylic
OUTER MATERIAL SPECIFICATION Nitrile, Nylon

COMPLIANCE

CE Cat. II
TP TC 019:2011

UKCA Cat. II
Information/UIS

EAC

EN 407:2020 (No flame protection) X1XXXX

EN 388:2016+A1:2018 4221A

EN ISO 21420:2020

EN 511:2006 X2X

ANSI 5 ABR

OEKO TEX® STANDARD 100 SE 14-214 RISE www.oeko-tex.com

ORIGINAL 04 EXCELLENT 2019 dermatest® dermatest-guarantee.de

Contact heat rating valid for palm area only

FEATURES

Warm lining

SIZE		ARTICLE NUMBER	EAN
7	S	8810-7	7340118321424
8	M	8810-8	7340118321448
9	L	8810-9	7340118321462
10	XL	8810-10	7340118321363
11	XXL	8810-11	7340118321387

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.