Date: 22/04/2024

PCS2PA 20 … 220 bar Adaptor G 1/4 A-M, Adaptor M20x1,5-F

Compact Pressure Switch

Item number: 48733833

Quantity: 1 pcs.

Order code: PCS2PA-BAQC-5ISZZZZZZ ZCKW
B018000IZZZZZZZZZ

Overview:
PCS2PA 20 … 220 bar Adaptor G 1/4 A-M, Adaptor M20x1,5-F
Compact Pressure Switch
PCS
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Piston Stainless Steel 316, O-Ring FPM
Connection: Stainless steel AISI 316L
contact version: 1xSPDT, silver contact
Setting range, working range, proof pressure: 20 … 220 bar, working range 0 … 350 bar, proof pressure 500 bar
Process connection: Adaptor G 1/4 A-M
Electrical connection: Adaptor M20x1,5-F
standard direct or wall mounting, fixing bore on the case

Ingress Protection: IP66
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 33.30
Repeatability of set point: ≤ 1% of end of setting range

1. set point: 180.00 bar increasing,

Details:
Compact Pressure Switch
Model PCS
Specifications according to data sheet: PV 33.30
Repeatability of set point: ≤ 1% of end of setting range
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Piston Stainless Steel 316, O-Ring FPM
1xSPDT, silver contact
20 … 220 bar, working range 0 … 350 bar, proof pressure 500 bar
Process connection: Adaptor G 1/4 A-M
Electrical connection: Adaptor M20x1,5-F
standard direct or wall mounting, fixing bore on the case
Approvals / Certificates: without
Switch standard: without
Brand: WIKA Instruments Italia
Ingress Protection: IP66
PCS2PA 20 … 220 bar
1. set point: 180.00 bar increasing,

© 2024 - WIKA Instruments s.a.r.l.