SKINDICHT® RWV-M

SKINDICHT® RWV-M, corrosion-resistant, metric angled gland plastic/metal, sealed by incised sealing ring

CE


Temperature-resistant


Connector with standard housing unit


Space requirement


Corrosion-resistant

Benefits
Strain relief
Sealed by incised sealing ring
Corrosion-resistant
Decrease in installation height
Seawater-resistant

Application range
Angled glands are used in areas where cables have to run in parallel to the housing wall.
Electric motor manufacturing
Machine and equipment manufacturing
Plant engineering
Light and sound applications

Product Make-up
Metric connection thread acc. to DIN EN 60423
Basis for technical information DIN IEC 62444

Note
Counter nut to be used: SKINDICHT® SM-M

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: Cable screw gland
Material:	Body: zinc die-casting, nickel-plated Compression screw and hexagon nut: nickel-plated brass Incised sealing ring: CR/NBR O-ring: NBR
Protection rating:	IP 55
Temperature range:	-20 °C to +100 °C

Last Update (06.07.2017)
©2017 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

SKINDICHT® RWV-M

Note
Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

Last Update (06.07.2017)
©2017 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

LAPP GROUP

PRODUCT INFORMATION

SKINDICHT® RWV-M

Article number	Article designation / size	Clamping range ØF (mm)	L	SW1	Ø A1	SW2	Ø A2	Ø G	Height (mm)	Total length C (mm)	Thread length, D (mm)	SW3
SKINDICHT® RWV-M												
52107800	M 12 x 1,5	5	20.5	14	16	12	13.2	8	5	26.1	11.5	17
52107810	M 16 x 1,5	9 - 3	23.5	18	20	16	17.6	12	5	28.6	11.5	22
52107820	M 20 x 1,5	13 - 4	28.5	22	24	20	22.2	15	5	35.1	12.5	27
52107830	M 25 x 1,5	17.5 - 8.5	31	27	29	25	27.5	20	5	38.1	13.5	32
52107840	M 32 x 1,5	25 - 16	33	34	36	32	35.2	27	5	44.6	13.5	41
52107850	M 40 x 1,5	32 - 23	43	42	45	40	43.5	35	5	53.1	15.5	46

Last Update (06.07.2017)
©2017 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16