Specifications

Eaton BK/SC-15

Catalog Number: BK/SC-15

Eaton Bussmann series SC fuse, Current-limiting time-delay fuse, Rejection style, 15 A, Class G, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 100 kAIC at 600 Vac, 10 kAIC at 170 Vdc, Bulk, 600 V, 170 Vdc



General specifications

Product Name
Eaton Bussmann series SC fuse

Catalog Number
BK/SC-15

UPC
051712750097

EAN
5027590455008

Product Length/Depth
0.41 in

Product Height
1.31 in

Product Width
0.41 in

Product Weight
0.1 lb

Warranty
Not Applicable

Compliances
Not Applicable
RoHS Compliant

Catalog Notes
Bulk

Powering Business Worldwide

Electrical rating

Amperage Rating

15 A

Interrupt rating

100 kAIC at 600 Vac

10 kAIC at 170 Vdc

Response time

12 sec at 200%

Voltage rating

600 Vac, 170 Vdc

Physical details

Packaging type

Standard

Bulk

General information

Class

Class G

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Special features

Rejection style

Resources

Catalogs

BK/SC-15~BK-SC-15~BUSS SC FUSE CLASS G

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - BK/SC-15

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia