

Comfort and protection in a safety shoe with unique BOA® Fit System and PU-coated and split leather upper.

jalas® ZENIT 1738

EN ISO 20345:2011 S3, SRC ASTM F2413-18 M/I/C SD 35 PR

Learn more

Comfort and protection in a soft safety shoe with unique BOA® Fit System and PU-coated and split leather upper. Excellent ergonomics and anti-static qualities for better fit and merino wool inner sole keeps feet dry. The RPU outer sole is oil resistant for outstanding grip. It features also our JALAS® aluminium toe cap, plasma-treated textile puncture protection and double impact protection zones in PORON® XRD®. Protection (S3).

CHARACTERISTICS

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

FUNCTIONS

- ProNose toe reinforcement
- Water repellent
- Oil-resistant outsole
- Anti-static properties
- Polstered shaft edge
- Ventilating insole
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)
- Quick-tie
- Stabilizator
- BOA® Fit System

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, environments with risk for outsole penetration

SPECIFICATION

TYPE Safety footwear, Low shoes
CATEGORY Cat. II
NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile
FITTING Regular
COLLECTION Zenit
UPPER MATERIAL PU-coated leather, Split leather
PRONOSE MATERIAL PU
TOECAP MATERIAL Aluminium
LINING MATERIAL Polyester, polyamide
INSOLE FX2 Climate
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Merino wool, Double shock absorption zones in Poron® XRD®
MIDSOLE MATERIAL PU midsole
OUTSOLE MATERIAL RPU outsole
FASTENING BOA® Fit System
COLOUR Black, Grey, Red
NET WEIGHT, (SIZE 42) 1.35 kg

COMPLIANCE

CE Cat. II

EN ISO 20345:2011
S3, SRC

EAC
TP TC 019:2011

ASTM F2413-18
M/I/C
SD 35 PR

ÖNORM Z 1259

DGUV 112-191

FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- ESD
- Aluminium toecap
- Oil-resistant outsole
- ProNose toe reinforcement
- Nail protection in plasma-treated composite (PTC) textile
- Water repellent
- Stabilizator

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
36	3	4	5	1738-36	6408487501432
37	4	5	6	1738-37	6408487501449
38	5	5½	6½	1738-38	6408487501456
39	6	6½	7½	1738-39	6408487501463
40	6½	7½	8½	1738-40	6408487501470
41	7	8	9	1738-41	6408487501487
42	8	9	10	1738-42	6408487501494
43	9	9½	11	1738-43	6408487501500
44	10	10½	11½	1738-44	6408487501517
45	10½	11	12½	1738-45	6408487501524
46	11	12	13	1738-46	6408487501531
47	12	13	14	1738-47	6408487501548

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.